KERN 572-30



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications



Measuring system				
Adjustment options:	External calibration			
Linearity:	3 mg			
Readability [d]:	1 mg			
Recommended adjusting weight:	200 g (F1)			
Repeatability:	1 mg			
Resolution:	240000			
Stabilisation time under laboratory conditions:	3 s			
Warm up time:	2 h			
Weighing capacity [Max]:	240 g			
Weighing system:	Strain gauge			
Weighing units:	tl (HK) g mo tl (Cn) lb tl (Singap. Malays) dwt ct oz tl (Tw) gn kg to t			
Display				
Display digit height (large):	1,800 cm			
Counting				
Counting resolution:	240000			
Mininum piece weight at piece counting (Laboratory:	1 mg			
Mininum piece weight at piece counting (Normal):	10 mg			

Functions				
Conversion function:	yes			
Counting function:	yes			
Percentage determination:	yes			
PRE-TARE function:	yes			
Suspended weighing:	Loop			
Vibration-free weighing (Animal	yes			
weighing program):				
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	10 °C			
Power supply				
Charging time:	10 h			
Input voltage:	100 V - 240 V			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH UK US			
Operating time (Backlight off):	30 h			
Operating time (Backlight on):	15 h			
Rechargeable battery:	Rchrg. battery optional			
· ·	0 7 1			
Services (optional)				
DAkkS Certificate:	963-127			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Precision balance			
· ·				
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	400 x 340 x 220 mm			
Gross weight:	4,400 kg			
Net weight:	2,300 kg			
Shipping method:	Parcel service			
Construction				
Casing material:	metal			
Dimensions housing (WxDxH):	180 x 310 x 85 mm			
Material weighing plate:	stainless steel			
Overall dimensions mounted	180 x 310 x 130 mm			
(WxDxH):				
Weighing space (ÃxH):	157 43			
	107 43			
Weighing surface (d):	106			

KERN 572-30



All-rounder e.g. as precision balance in the laboratory or in harsh industrial applications

Piktogramme

STANDARD

CAL EXT	• ###4.• RS 232	GLP PRINTER	PCS	% Percent	MOVE	UNDER
B H	DMS	1 DAY				

OPTION

