KERN ABS80-4N



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]



Measuring system

Adjustment options:	External calibration			
Linearity:	0,300 mg			
Minimum weight (USP):	400 mg			
Readability [d]:	0,100 mg			
Recommended adjusting weight:	80 g (E2)			
Repeatability:	0,200 mg			
Resolution:	820000			
Stabilisation time under laboratory conditions:	3 s			
Warm up time:	4 h			
Weighing capacity [Max]:	82 g			
Weighing units:	g ct mg			

Display

Display digit height (large):

Counting	
Counting resolution:	82000
Mininum piece weight at piece counting (Laboratory:	1 mg
Mininum piece weight at piece counting (Normal):	10 mg

1,400 cm

Reference weight:	yes			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Percentage determination:	yes			
Standby function:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	85 %			
Maximum operating temperature:	30 °C			
Minimum ambient temperature:	10 °C			
Minimum humidity:	20 %			
Power supply				
Input voltage:	110 V - 230 V AC			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH UK US			
Services (optional)				
DAkkS Certificate:	963-101			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Analytical balance			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	390 x 560 x 530 mm			
Gross weight:	9 kg			
Net weight:	6 kg			
Shipping method:	Parcel service			
Construction				
Casing material:	Plastic			
Dimensions draft shield (WxDxH):	201 x 220 x 256 mm			
Dimensions housing (WxDxH):	210 x 340 x 325 mm			
Level indicator:	yes			
Material weighing plate:	stainless steel			
Revolving screw feet:	yes			
Weighing space (WxDxH):	174 x 162 x 227 mm			
Weighing surface (d):	91			

KERN ABS80-4N



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]

Piktogramme

STANDARD

MULTI SC TECH 1 DAY

	GLP PRINTER	DCC.		<u>%</u>		
	 PRINTER	FLS	RELIFE	PERCENT	TUL	UNIT

OPTION



FACTORY

