KERN ACJ80-4M



The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]



Measuring system

Adjustment options:	Internal calibration (manual) Internal calibration (auto)
Linearity:	0,300 mg
Minimum weight (USP):	400 mg
Readability [d]:	0,100 mg
Repeatability:	0,200 mg
Resolution:	820000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	4 h
Weighing capacity [Max]:	82 g
Weighing units:	g mg
Display	

Display digit height (large):

Technical data about verification

Minimum load [Min]:	10 mg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes

Verification by KERN possible:	yes
Verification class:	
Verification value [e]:	1 mg
Counting	
Counting resolution:	82000
Mininum piece weight at piece	1 mg
counting (Laboratory:	10
Mininum piece weight at piece counting (Normal):	10 mg
Reference weight:	yes
Functions	
Counting function:	yes
Function to save totals:	yes
Percentage determination:	yes
Standby function:	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	85 %
Maximum operating temperature:	30 °C
Minimum ambient temperature:	10 °C
Minimum humidity:	20 %
Power supply	
Input voltage:	110 V - 230 V AC
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Services (optional)	
DAkkS Certificate:	963-101
Verification:	965-201
Category	
Brand:	KERN
Category:	Balances
Product Group:	Analytical balance
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	390 x 565 x 520 mm
Gross weight:	8,900 kg
Net weight:	6,100 kg
	Derecterrice

Shipping method:

1,400 cm

Parcel service

KERN ACJ80-4M

KERN

The bestseller in analytical balances, with high-quality single-cell weighing system, also with EC type approval [M]

Construction

Dimensions draft shield (WxDxH):	201 x 220 x 256 mm
Dimensions housing (WxDxH):	210 x 340 x 325 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing space (WxDxH):	174 x 162 x 227 mm
Weighing surface (d):	91

Piktogramme

STANDARD



OPTION



FACTORY

