# KERN CCS60K0.01L.







Measuring system	
Adjustment options:	External calibration
Linearity:	50 mg
Recommended adjusting weight:	50000 g (M1)
Repeatability:	20 mg
Stabilisation time under laboratory conditions:	2 s
Weighing system:	Strain gauge
Weighing units:	lb kg

Display

Display digit height (large):

Counting	
Counting resolution:	1200000
Mininum piece weight at piece counting (Laboratory:	50 mg
Mininum piece weight at piece counting (Normal):	500 mg
Reference weight:	yes

2 cm

Functions		
Conversion function:	yes	
Counting function:	yes	
Function to save totals:	yes	
PRE-TARE function:	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	EURO CH UK US
Operating time (Backlight off):	60 h
Operating time (Backlight on):	70 h
Rechargeable battery:	Rchrg. battery optional

Servi	ces (	optionai	)

Adjustment at the location of installation: abhängig von

Auflösung/Max | depends on resolution and capacity

DAkkS Certificate: 962-129-127

$\circ$		ory	
1 2	$t \wedge \alpha$	$\Delta m$	
1070	11.549	LWIE	

Brand: KERN

Product Group: Counting system

### Packaging & shipping

Delivery: 48 h

Dimensions packaging (WxDxH): 1040 x 640 x 230 mm

Gross weight: 19 kg
Net weight: 16 kg

Shipping method: Parcel service

### Construction

1,500 m Cable length: Cable length of display device: 5 m Casing material: **Plastic** 500 x 400 x 137 mm Dimensions of weighing plate (WxDxH): Level indicator: yes Material weighing plate: stainless steel Overall dimensions mounted 320 x 330 x 125 mm (WxDxH): Revolving screw feet: yes Weighing surface (WxD): 500 x 400 mm

## Piktogramme

#### STANDARD





