KERN CKE16K0.1



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution up to 360,000 points - now also with KERN KCP and stronger battery operation



| Measuring system | | | | |
|---|--|--|--|--|
| Adjustment options: | External calibration | | | |
| Linearity: | 300 mg | | | |
| Readability [d]: | 100 mg | | | |
| Recommended adjusting weight: | 16 kg (F1) | | | |
| Repeatability: | 100 mg | | | |
| Resolution: | 160000 | | | |
| Stabilisation time under laboratory conditions: | 3 s | | | |
| Tare range: | 16 kg | | | |
| Warm up time: | 2 h | | | |
| Weighing capacity [Max]: | 16 kg | | | |
| Weighing system: | Strain gauge | | | |
| Weighing units: | g lb dwt custom factor oz gn kg PCS ozt | | | |
| Display | | | | |
| Display digit height (large): | 2,500 cm | | | |
| Counting | | | | |
| Counting resolution: | 160000 | | | |
| Mininum piece weight at piece counting (Laboratory: | 100 mg | | | |
| Mininum piece weight at piece counting (Normal): | 1 g | | | |
| Reference weight: | yes | | | |
| | | | | |

| Functions | | |
|--------------------------------|-----|--|
| Counting function: | yes | |
| PRE-TARE function: | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | |
|---------------------------------|----------------------------------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | 10 °C |
| Power supply | |
| Battery: | 6x1.5 V AAA |
| Charging time: | 10 h |
| Input voltage: | 110 V - 240 V AC |
| Mains adapter: | Mains adapter external |
| Mains adapter/adapter included: | EURO CH UK US |
| Operating time: | 80 h |
| Operating time (Backlight off): | 90 h |
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional - intern |
| Services (optional) | |
| DAkkS Certificate: | 963-128 |
| Category | |
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Counting scale |
| Packaging & shipping | |
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 470 x 470 x 190 mm |
| Gross weight: | 7,600 kg |
| Net weight: | 6,500 kg |
| Shipping method: | Parcel service |
| Construction | |
| Dimensions housing (WxDxH): | 350 x 390 x 120 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Develving earous feets | |
| Revolving screw feet: | yes |

KERN CKE16K0.1



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution up to 360,000 points - now also with KERN KCP and stronger battery operation

Piktogramme

STANDARD

| | | | | | | + • ?) | | B |
|---------|--------|----------|---------|-----|------|-----------|------|-------|
| CAL EXT | RS 232 | PROTOCOL | PRINTER | PCS | UNIT | TOL | BATT | MULTI |
| UNDER | DMS | 1 DAY | | | | | | |

OPTION



FACTORY

