KERN SFB100K-2HM



Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]



Measuring system

Adjustment options:	External calibration			
Linearity:	50 g			
Load cell connection:	6-wire			
Readability [d]:	50 g			
Recommended adjusting weight:	120 kg (M1)			
Repeatability:	50 g			
Resolution:	3000			
Stabilisation time under laboratory conditions:	2 s			
Tare range:	150 kg			
Warm up time:	10 min			
Weighing capacity [Max]:	150 kg			
Weighing system:	Strain gauge			
Weighing units:	kg			
Display				

Display digit height (large):

5,200 cm

-				
Technical data about verification				
Minimum load [Min]:	1 kg			
Periodic Verification for Italy:	969-112			
Verification approval conforming to 2014/31/EU:	yes			
Verification by KERN possible:	yes			
Verification class:	III			
Verification value [e]:	50 g			
Functions				
Counting function:	yes			
Function to save totals:	yes			
Vibration-free weighing (Animal weighing program):	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	95 %			
Maximum operating temperature:	40 °C			
Minimum ambient temperature:	-10 °C			
Minimum humidity:	0 %			
Power supply				
Charging time:	12 h			
Input voltage:	110 V - 230 V AC			
Mains adapter:	Mains adapter external			
Mains adapter/adapter included:	EURO CH AUS UK US			
Operating time (Backlight off):	35 h			
Operating time (Backlight on):	20 h			
Services (optional)				
Adjustment at the location of installation	:961-249			
DAkkS Certificate:	963-129			
Verification:	965-229			
	000 220			
Category				
Brand:	KERN			
Category:	Balances			
Product Group:	Industiral scale			
Packaging & shipping				
Delivery:	24 h			
Dimensions packaging (WxDxH):	795 x 465 x 220 mm			
Gross weight:	14,100 kg			
Net weight:	9,700 kg			
Shipping method:	Parcel service			
UN number:	2800			

KERN SFB100K-2HM

Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]



Construction				
Cable length:	2,500 m			
Cable length of display device:	0 mm			
Dimensions of display device (WxDxH):	266 x 165 x 96 mm			
Dimensions of weighing plate (WxDxH):	400 x 300 x 128 mm			
of stand:	40 cm			
Level indicator:	yes			
Material weighing plate:	stainless steel			
Overall dimensions mounted (WxDxH):	400 x 460 x 590 mm			
Revolving screw feet:	yes			
Wall mount:	yes			
Weighing surface (WxD):	400 x 300 mm			

Piktogramme

STANDARD

	GLP			666	666			
CAL EXT	PROTOCOL	PCS	TOL	IP 65	IP 67	ACCU	MULTI	DMS
1 DAY								

OPTION

DAkks +3 days

FACTORY

