KERN SFB30K10HIPM



Stainless steel platform balance with dust and spray protection to IP65 and EC type approval IMI



Measuring system	
Adjustment options:	External calibration
Linearity:	10 g
Load cell connection:	6-wire
Readability [d]:	10 g
Recommended adjusting weight:	30 kg (M1)
Repeatability:	10 g
Resolution:	3000
Stabilisation time under laboratory conditions:	2 s
Tare range:	-30 kg
Warm up time:	10 min
Weighing capacity [Max]:	30 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height (large):

Technical data about verification	
Minimum load [Min]:	200 g
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	10 g
Functions	
Counting function:	yes
Function to save totals:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	95 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	12 h
land the sales	
Input voltage:	110 V - 230 V AC
Mains adapter:	110 V - 230 V AC Mains adapter external
•	
Mains adapter:	Mains adapter external
Mains adapter: Mains adapter/adapter included:	Mains adapter external EURO CH AUS UK US
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off):	Mains adapter external EURO CH AUS UK US 35 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on):	Mains adapter external EURO CH AUS UK US 35 h 20 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional)	Mains adapter external EURO CH AUS UK US 35 h 20 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation	Mains adapter external EURO CH AUS UK US 35 h 20 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate:	Mains adapter external EURO CH AUS UK US 35 h 20 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification:	Mains adapter external EURO CH AUS UK US 35 h 20 h
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category	Mains adapter external EURO CH AUS UK US 35 h 20 h n: 961-248 963-128 965-228
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand:	Mains adapter external EURO CH AUS UK US 35 h 20 h 1: 961-248 963-128 965-228 KERN
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category:	Mains adapter external EURO CH AUS UK US 35 h 20 h 1:961-248 963-128 965-228 KERN Balances
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group:	Mains adapter external EURO CH AUS UK US 35 h 20 h 1:961-248 963-128 965-228 KERN Balances
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping	Mains adapter external EURO CH AUS UK US 35 h 20 h 1:961-248 963-128 965-228 KERN Balances Industiral scale
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery:	Mains adapter external EURO CH AUS UK US 35 h 20 h 1:961-248 963-128 965-228 KERN Balances Industiral scale
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	Mains adapter external EURO CH AUS UK US 35 h 20 h n: 961-248 963-128 965-228 KERN Balances Industiral scale
Mains adapter: Mains adapter/adapter included: Operating time (Backlight off): Operating time (Backlight on): Services (optional) Adjustment at the location of installation DAkkS Certificate: Verification: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	Mains adapter external EURO CH AUS UK US 35 h 20 h 1:961-248 963-128 965-228 KERN Balances Industiral scale 24 h 700 x 410 x 220 mm 9,370 kg

5,200 cm

KERN SFB30K10HIPM



Stainless steel platform balance with dust and spray protection to IP65 and EC type approval [M]

Construction	
Cable length of display device:	0 mm
Dimensions of display device (WxDxH):	266 x 165 x 96 mm
Dimensions of weighing plate (WxDxH):	300 x 240 x 100 mm
of stand:	40 cm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	300 x 400 x 390 mm
Revolving screw feet:	yes
Weighing surface (WxD):	300 x 240 mm

Piktogramme

STANDARD





















OPTION



FACTORY



