

SENCITY® Spot-M 2x2 WiFi MIMO Antenna 1324.17.0117

Description

Directional high gain antenna for Wi-Fi 1/Wi-Fi 3 bands.
 Supports 2X2 WiFi MIMO.
 Supports from 2.3 GHz to 2.7 GHz frequency bands.
 Vertical and horizontal polarized.
 For outdoor or indoor applications.



Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	2300 - 2700
VSWR	2
Impedance (Ohm)	50
Gain (dBi)	14
3dB beamwidth (h) (°)	35
3dB beamwidth (v) (°)	35
Composite power max (W)	6
Ambient temperature (°C)	25
Front to back ratio (dB)	25
Co/Crosspolar ratio (dB)	15
Vertical electrical tilt (°)	0
Port Isolation (dB)	20

Ports

	Port 1	Port 2
Port name	VER	HOR
Connector	N, jack (female)	N, jack (female)
Polarization	vertical	horizontal
DC grounded	Yes	Yes

Connections

	Band 1
Port 1	X
Port 2	X

General Data

Mechanical Data

Dimensions (mm) 190 x 190 x 30 (Height x Width x Depth)
 Weight (kg) 0.5
 Windload frontal: 105 N at 160 km/h, lateral: 16 N at 160 km/h , Wind speed survival: 220 km/h

Environmental Data

Environmental conditions indoor/outdoor
 Operation temperature (°C) -55 to 70
 Storage temperature (°C) -55 to 70
 Transport temperature (°C) -55 to 70

SENCITY® Spot-M 2x2 WiFi MIMO Antenna 1324.17.0117

IP rating	IP67
Flammability rating	UL 94-HB
Solar radiation 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	ASTM 653-96 compliant
Lead-free soldered	yes
WEEE 2012/19/EU REACH 1907/2006/EC	special marking needed compliant

Low temperature IEC 60068-2-1 72h -55°C
High temperature IEC 60068-2-2 72h +71°C
Temperature cycling IEC 60068-2-14 1h -45 to +70°C 3 cycles
Humidity ETSI EN300-2-4 T4.1E 144h 95%
Solar radiation ASTM G53 1000 h
Salt spray IEC 60068-2-11 Ka 500 h
Mechanical shock IEC 60721-3-4 4M5
Vibration IEC 60721-3-4 30 min/axis random 4M5

Material Data

Radome colour	RAL 9002 (grey-white)
Radome material	Plastic
Back plate/base plate material	Aluminium

Related Products

9091.99.0201 Planar Antenna Downtilt Bracket

Related Documents

Mounting instruction	DOC-0000225623
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DPR-00360608
3D-model	DOC-0000814014