

SAFETY DATA SHEET FLUXCLENE Aerosol

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

 PRODUCT NAME
 FLUXCLENE Aerosol

 PRODUCT NO.
 EFLU200/400D

APPLICATION Manufacture of electrical equipment

SUPPLIER ELECTROLUBE. A division of

HK WENTWORTH LTD KINGSBURY PARK, MIDLAND

ROAD

SWADLINCOTE

DERBYSHIRE, DE11 0AN UNITED KINGDOM +44(0)1283 222 111 +44(0)1283 550 177 info@hkw.co.uk

2 HAZARDS IDENTIFICATION

Highly flammable.

Vapours may cause drowsiness and dizziness.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. F;R11. N;R50/53. R67.

PHYSICAL AND CHEMICAL HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CYCLOHEXANE	203-806-2	110-82-7	30-60%	F;R11 Xn;R65 Xi;R38 R67 N;R50/53
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	10-30%	R10
HEXANE MIXTURE OF ISOMERS (MAX 5%			5-10%	F;R11 Xn;R65 Xi;R38 R67 N;R51/53
n-HEXANE (203-777-6))				
HEPTANE	205-563-8	142-82-5	1-5%	F;R11 Xn;R65 Xi;R38 R67 N;R50/53
d-LIMONENE	227-813-5	5989-27-5	1-5%	R10 R43 Xi;R38 N;R50/53
HEXANE-norm	203-777-6	110-54-3		F;R11 Repr3;R62 Xn;R65,R48/20 Xi;R38 R67 N;R51/53

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

Report Date : 20/11/2008

REVISION DATE: NOVEMBER 2008

FLUXCLENE Aerosol

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

INGESTION

Not relevant.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Provide good ventilation.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)	
CYCLOHEXANE	WEL	100 ppm	350 mg/m3	300 ppm	1050 mg/m3	
HEPTANE	WEL	500 ppm				
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

Report Date : 20/11/2008
REVISION DATE: NOVEMBER 2008

FLUXCLENE Aerosol

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol Liquid
COLOUR Colourless
ODOUR Lemon
VOLATILITY DESCRIPTION Volatile.

SOLUBILITY Insoluble in water

BOILING POINT (°C) >80 (176 F) **MELTING POINT (°C)** <-29 (-20.2 F)

RELATIVE DENSITY 0.780 @ 20 °c (68 F) **VAPOUR PRESSURE** 11.52 kPa @ 20 °c (68 F)

FLASH POINT (°C) 0 (32 F) CC (Closed cup). **AUTO IGNITION** > 200 (392 F)

TEMPERATURE (°C)

FLAMMABILITY LIMIT - LOWER(%) 0.6 FLAMMABILITY LIMIT - UPPER(%) 8.3

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalies.

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

222 mg/kg (ivn-mouse)

EYE CONTACT

Irritating to eyes.

Other Health Effects

This substance has no evidence of carcinogenic properties.

ROUTE OF ENTRY

Skin and/or eye contact. Inhalation.

Toxic Dose 1 - LD 50

Name HEPTANE

 Toxic Conc. - LC 50
 103 ppm/4h (inh-rat)

 Name
 CYCLOHEXANE

 Toxic Dose 1 - LD 50
 12705 mg/kg (oral rat)

 Toxic Dose 2 - LD 50
 813 mg/kg (oral-mouse)

 Name
 HEXANE-norm

 Toxic Dose 1 - LD 50
 28700 mg/kg (oral rat)

 Toxic Conc. - LC 50
 48000 ppm/4h (inh-rat)

 Name
 PROPAN-2-OL

 Toxic Dose 1 - LD 50
 5045 mg/kg (oral rat)

 Toxic Dose 2 - LD 50
 3600 mg/kg (oral-mouse)

 Toxic Conc. - LC 50
 47-73 mg/l/4h (inh-rat)

 Name
 1-METHOXY-2-PROPANOL

 Toxic Dose 1 - LD 50
 5200 mg/kg (oral rat)

 Toxic Dose 2 - LD 50
 11700 mg/kg (oral-mouse)

Name d-LIMONENE

Toxic Dose 1 - LD 50 >5000 mg/kg (oral rat)

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

Report Date : 20/11/2008
REVISION DATE: NOVEMBER 2008

FLUXCLENE Aerosol

Name HEPTANE LC 50, 96 Hrs, FISH mg/l 4.924

Name CYCLOHEXANE

LC 50, 96 Hrs, FISH mg/l 42.3

Name PROPAN-2-OL

LC 50, 96 Hrs, FISH mg/l 9600
EC 50, 48 Hrs, DAPHNIA, mg/l 10000

Name 1-METHOXY-2-PROPANOL

LC 50, 96 Hrs, FISH mg/l 20800
EC 50, 48 Hrs, DAPHNIA, mg/l 23300

Name d-LIMONENE

EC 50, 48 Hrs, DAPHNIA, mg/l 12.3

Mobility

The product has poor water-solubility.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Empty containers must not be burned because of explosion hazard.

14 TRANSPORT INFORMATION



UK ROAD CLASS 2

PROPER SHIPPING NAME AEROSOLS

 UN NO. ROAD
 1950
 UK ROAD PACK GR.
 N/A

ADR CLASS NO. 2 ADR CLASS Class 2: Gases

ADR PACK GROUP ADR LABEL NO. 2.1 N/A CEFIC TEC(R) NO. RID CLASS NO. 20G5F 2 RID PACK GROUP N/A UN NO. SEA 1950 IMDG CLASS IMDG PACK GR. 2.1 N/A **EMS** F-D, S-U MFAG See Guide MARINE POLLUTANT No. UN NO. AIR 1950 AIR CLASS AIR PACK GR. 2.1 N/A

15 REGULATORY INFORMATION

SYMBOLS



Irritant



Highly Flammable



Dangerous for the environment

CONTAINS d-LIMONENE

RISK PHRASES

R11 Highly flammable.

R43 May cause sensitisation by skin contact.

R36/38 Irritating to eyes and skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Report Date : 20/11/2008

REVISION DATE: NOVEMBER 2008

FLUXCLENE Aerosol

SAFETY PHRASES

A1 Pressurised container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use.

A2 Do not spray on a naked flame or any incandescent material.

S2 Keep out of the reach of children

S9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S24/25 Avoid contact with skin and eyes.

S51 Use only in well-ventilated areas.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 1988.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution Act 1974.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE NOVEMBER 2008

REV. NO./REPL. SDS 3

GENERATED

SDS NO. 10371

RISK PHRASES IN FULL

R10 Flammable.
R11 Highly flammable.
R36 Irritating to eyes.
R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R65 Harmful: may cause lung damage if swallowed.
R67 Vapours may cause drowsiness and dizziness.

Report Date : 20/11/2008

REVISION DATE: NOVEMBER 2008

FLUXCLENE Aerosol

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.