## onsemi

Final Product/Process Change Notification Document #:FPCN24325X Issue Date:12 Oct 2021

Title of Change:	Add Plasma Clean prior	r to Mold process (Industrial)	
Proposed First Ship date:	19 Jan 2022 or earlier i	f approved by customer	
Contact Information:	Contact your local onse	emi Sales Office or David.Craig@onsemi.com	
PCN Samples Contact:	Contact your local onsemi Sales Office or < <u>PCN.samples@onsemi.com</u> >. Sample requests are to be submitted no later than 30 days from the date of first notification, Initial PCN or Final PCN, for this change. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.		
Additional Reliability Data:	Contact your local onsemi Sales Office or Nicky.Siu@onsemi.com		
Type of Notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change. onsemi will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact PCN.Support@onsemi.com		
Marking of Parts/ Traceability of Change:	Same		
Change Category:	Assembly Change		
Change Sub-Category(s):	Manufacturing Process	Change	
Sites Affected:			
onsemi Sites		External Foundry/Subcon Sites	
onsemi Carmona, Philippines		None	
Description and Purpose: Pre-mold plasma clean operation is being add There are no product material changes as a resu There is no product marking change as a resu	esult of this change.	ss to improve adhesion.	
Reliability Data Summary:			
QV DEVICE NAME: NCV57255DR2G RMS: 068223 PACKAGE: SOIC-16W			

PACKAGE: SOIC-16W

Test	Specification	Condition	Interval	Results
HAST	JESD22-A110	130°C, 85% RH, 18.8psig, bias	192 hrs	0/231
HTBB		Ta= 125 °C	2016 hrs	0/231
HTOL	JESD22-A108	Ta = 125 °C, 100 % max rated Vcc	2016 hrs	0/231
HTSL	JESD22-A103	Ta= 150 °C	2016 hrs	0/231
HVTHB		85 °C, 60% RH	336 hrs	0/231
PC	J-STD-020 JESD-A113	MSL 1 @ 260 °C		0/231
RSH	JESD22- B106	Ta = 265C, 10 sec		0/30
SAT		Precon Level = MSL 1 @ 260 °C		0/75
SD	JSTD002	Ta = 245C, 5 sec		0/45



Final Product/Process Change Notification Document #:FPCN24325X Issue Date:12 Oct 2021

TC	JESD22-A104	Ta= -65 °C to +150 °C	1000 cyc	0/231
uHAST	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	192 hrs	0/231
Electrical Cha	racteristics Summary:			
Electrical chara	acteristics are not impacted.			
-				
	standard (off the shelf) part numbe	rs are listed in the parts list. Any custom parts affected b on, or on the <b>PCN Customized Portal</b> .	by this PCN are showr	n in the customer
Note: Only the	standard (off the shelf) part numbe	on, or on the <u>PCN Customized Portal</u> .	by this PCN are showr cation Vehicle	n in the customer
Note: Only the	standard (off the shelf) part numbo Idendum in the PCN email notificat	on, or on the <u>PCN Customized Portal</u> . Qualifi		n in the customer
Note: Only the	standard (off the shelf) part numbe Idendum in the PCN email notificati Part Number	on, or on the <u>PCN Customized Portal</u> . Qualifi NCV	cation Vehicle	n in the customer
Note: Only the	standard (off the shelf) part numbe Idendum in the PCN email notificati Part Number NCD57080CDR2G	on, or on the <u>PCN Customized Portal</u> . Qualifi NCV	cation Vehicle 57255DR2G	n in the customer
Note: Only the	standard (off the shelf) part number Idendum in the PCN email notification Part Number NCD57080CDR2G NCD57080BDR2G	on, or on the <u>PCN Customized Portal</u> . Qualifi NCV NCV	cation Vehicle 57255DR2G 57255DR2G	n in the customer