



Features:

- Cable to CW1308 are replacing cables to CW1293 and have a much improved colour coding system in which all cores are bi-coloured with the base colour of one wire of a pair being the band colour of the other.
- Concentric layers are used for up to 25 pairs, but by using unit construction coupled with the improved colour code, cables of up to 128 pairs are available.
- CW1308 cables are used for cable equipment 2000 designed to cater for the new distribution networks and digital systems.

Cables depending on their constructional methods are used as follows:

- Layer construction-for general use.

Construction:

- Tinned solid copper conductors, PVC insulated, PVC oversheathed.
- A non-metallic rip-cord is laid under the oversheath to facilitate its removal.
- The preferred sheath colour is white although cream, grey or black sheaths.

Conductor			Insulation (PVC)	
Nominal Area (mm ²)	Size	Maximum Resistance at 20°C (ohm/km)	Minimum Radial Thickness	Maximum Overall Diameter
0.196	1/0.5	97.8	0.15	0.95

Dimensions : Millimetres

Specifications

Conductor Size	Number of Pairs	Sheath		Cable (M)	Part Number
		Minimum Radial Thickness	Maximum Diameter		
1/0.5	2	-	-	100	CBBR0101
	3	0.6	4.8		CBBR0104
	6		6.8		CBBR0108
	10		8.3		CBBR0109
	4	0.5	5.8		CBBR0107

Dimensions : Millimetres (Unless Specified)

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-Power is the registered trademark of the Group. © Premier Farnell plc 2009.