

tesa® Professional 53988 Soft PVC Insulation Tape



Product Information

tesaflex 53988 Soft PVC Insulation Tape, certified according to IEC 60454-3-1 / 5 Norm

The electric insulation tape tesaflex 53988 is a reliable helper for electricians, mechanics and other handymen. It is characterized by its relatively thick base material, a high degree of flexibility and a very good adhesive performance (even on steel and at low temperatures).

Features

- Certified according to IEC 60454-3-1 (VDE, IMQ, SEMKO), VOC-certified, RoHS 2.0 and REACH conform
- Thick backing material (150 µm)
- High dielectric breakdown voltage (7.000 V)
- Heat-resistant up to +90° C
- Available in many different colors and dimensions

Application

- Ideally suited for electrical applications, e.g. insulating or marking wires

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	soft PVC	• Tensile strength	25 N/cm
• Total thickness	150 µm	• Temperature resistance	90 °C
• Type of adhesive	natural rubber	• Temperature resistance short term	90 °C
• Elongation at break	240 %	• Dielectric breakdown voltage	7000 volt

Adhesion to

- steel 2.5 N/cm

Properties

• Hand tearability	●●●	• Humidity resistance	●●●
• Easy to remove	no	• Softener resistance	●●●
• Certified according to	VDE, IMQ, SEMKO, IEC 60454-3-1	• UV-resistance	●●
• Tack	●●●●	• Water resistant	●●
• Abrasion resistance	●●●	• Conformability	●●●●
• Ageing resistance (UV)	●●●	• Fogging	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit
<http://l.tesa.com/?ip=53988>

tesa® Professional 53988 Soft PVC Insulation Tape



Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=53988>