

tesaflex® 4163



product information

Multipurpose Soft PVC Premium

tesa® 4163 is a specially formulated Soft PVC tape with a good film flexibility. Due to the UV stable acrylic adhesive it is suitable for permanent applications.

Main Application

tesaflex® 4163 is ideal for the following applications:

- Installation
- Repairing
- Marking
- Splicing
- Bundling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	soft PVC	• Type of liner	replpable
• Total thickness	130 µm	• Temperature resistance	siliconised paper
• Type of adhesive	acrylic	• UV-resistance	105 °C
• Elongation at break	250 %	• Dielectric breakdown voltage	104 weeks
• Tensile strength	30 N/cm		7000 volt

Adhesion to

- steel 1.8 N/cm

Properties

- Certified according to US 302

Additional Information

It conforms to US safety standard 302. The isogenogrey colour is suitable for instalation of water pipes.

tesaflex® 4163

product information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04163>