# Time-Lag SMD Fuses 11.3mm × 4mm



RoHS

**Compliant** 

### **Specifications**

Main Characteristics : Brick fuse; Time-Lag (T)

Standard : UL-248-14 Body Material : Ceramic

End Caps Material : Copper plated with silver

Operating Temperature : -55°C to +125°C Stock Temperature : +10°C to +60°C

Relative humidity:≤75% yearly average Without dew, maximum 30 days at 95% Vibration Resistance : 24 cycles at 15 min. each (60068-6)

Vibration Resistance : 24 cycles at 15 min. each (60068-6) 10-60Hz at 0.75mm amplitude

60-2000Hz at 10g acceleration : 260°C.≤10 sec (Wave Soldering)

Soldering Parameters : 260°C.≤10 sec (Wave Soldering) 300°C.≤2 sec (Hand Soldering)


Soldering Peak: 260°C. 10 sec.

280°C. 5 sec. (IEC 60068-20)

#### **Time Vs Current Characteristic**

| Rated Current | 100% | 200% |  |
|---------------|------|------|--|
| 1A to 2A      | >4H  | <60s |  |

## Average Time Current (I-T) Curves



#### Electrical Characteristics at 25°C

| Amp<br>Code | Rated<br>Current | Rated<br>Voltage<br>DC                   | Max.<br>Voltage Drop<br>(mV) | Typ. Cold<br>Resistance<br>(mΩ) | Typ.<br>Melting<br>I²t(A²sec) | Breaking<br>Capacity   |
|-------------|------------------|--|------------------------------|---------------------------------|-------------------------------|--|
| 1100        | 1A               | 125V AC                                  | 150                          | 108                             | 6.25                          | 150A@125V AC   |
| 1200        | 2A               | 250V AC<br>125V DC<br>250V DC<br>350V DC | 100                          | 37                              | 17.6                          | 150A@250V AC<br>150A@125V DC<br>150A@250V DC<br>100A@350V DC |

#### Note:

- (1) Permissible continuous operating current is ≤100% at ambient temperature of 23°C (73.4°F)
- (2) The current values used for calculating I2T should be within the standard range of 8ms~10ms.


Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro




# Time-Lag SMD Fuses 11.3mm × 4mm



#### Diagram





### **Part Number Table**

| Description  | Part Number |
|--|-------------|
| SMD Fuse, Time-Lag , 1A, 250V AC / 400V DC, 11.3mm × 4mm | MP006278    |
| SMD Fuse, Time-Lag , 2A, 250V AC / 400V DC, 11.3mm × 4mm | MP006279    |

**Dimensions: Millimetres** 

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

