# 2377783-3 - ACTIVE

TE Internal #: 2377783-3 Housing for Male Terminals, Wire-to-Wire, 36 Position, .157 in / .165 in [4.2 mm / 4 mm] Centerline, Green, Wire & Cable, Power & Signal, Bulkhead

#### View on TE.com >

connectivity

Connectors > Automotive Connectors > Connector Housings



Connector & Housing Type: Housing for Male Terminals

Mating Tab Width: 1.6 mm [.063 in ]

Connector System: Wire-to-Wire

Number of Positions: 36

Centerline (Pitch): 4 mm, 4.2 mm [.157 in, .165 in ]

#### Features

#### Product Type Features

| Connector & Housing Type          | Housing for Male Terminals |
|-----------------------------------|----------------------------|
| Connector System                  | Wire-to-Wire               |
| Sealable                          | No                         |
| Hybrid Connector                  | No                         |
| Primary Locking Feature           | Locking Lance              |
| Connector & Contact Terminates To | Wire & Cable               |
| Configuration Features            |                            |
| Number of Positions               | 36                         |
| Number of Rows                    | 4                          |
| Electrical Characteristics        |                            |
| Nominal Voltage Architecture      | 36 V                       |
| Body Features                     |                            |
| Cable Exit Angle                  | 180°                       |
| Body Material                     | PAGF                       |
|                                   |                            |

### 2377783-3

Housing for Male Terminals, Wire-to-Wire, 36 Position, .157 in / .165 in [4.2 mm / 4 mm] Centerline, Green, Wire & Cable, Power & Signal, Bulkhead



| Primary Product Color       | Green                          |
|-----------------------------|--------------------------------|
| Connector Code              | С                              |
| Contact Features            |                                |
| Mating Tab Width            | 1.6 mm[.063 in]                |
| Mechanical Attachment       |                                |
| Connector Mounting Type     | Bulkhead                       |
| Housing Features            |                                |
| Centerline (Pitch)          | 4 mm, 4.2 mm[.157 in][.165 in] |
| Usage Conditions            |                                |
| Operating Temperature (Max) | 120 °C[248 °F]                 |
| Operating Temperature Range | -40 - 120 °C[-40 - 248 °F]     |
| Operation/Application       |                                |
| Circuit Application         | Power & Signal                 |
| Industry Standards          |                                |
| UL Flammability Rating      | UL 94HB                        |
| Other                       |                                |
|                             |                                |

| $\sim$ | ~ ~ | ٠  |             |        |  |  |
|--------|-----|----|-------------|--------|--|--|
|        | 00  | 11 | $\sim \sim$ | $\sim$ |  |  |

Voc

| Serviceable                          | res |  |
|--------------------------------------|-----|--|
| Connector Position Assurance Capable | No  |  |

# Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2022<br>(223)<br>Candidate List Declared Against: JUL 2021<br>(219)<br>SVHC > Threshold:<br>Not Yet Reviewed |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.  |
| Solder Process Capability                     | Not reviewed for solder process capability  |

## 2377783-3

Housing for Male Terminals, Wire-to-Wire, 36 Position, .157 in / .165 in [4.2 mm / 4 mm] Centerline, Green, Wire & Cable, Power & Signal, Bulkhead



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# **Customers Also Bought**





#### 2377783-3

Housing for Male Terminals, Wire-to-Wire, 36 Position, .157 in / .165 in [4.2 mm / 4 mm] Centerline, Green, Wire & Cable, Power & Signal, Bulkhead



TE Part #2311283-2 36POS,MCON 1.2,REC HSG ASSY,SLD

## Documents

Product Drawings 36POS,AMP MCP 1.5K,TAB HSG ASSY,UNSLD

English

**CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2377783-3\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2377783-3\_A.3d\_igs.zip

English

Customer View Model

#### ENG\_CVM\_CVM\_2377783-3\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English