Twisted Pair Transmission System

pro-signal

Features

- BNC male to RJ45 female
- Passive Video Transceiver (no power required)
- Transmission Range: Colour 400m, B/W 600m (via CAT 5 UTP Cable)
- Designed for CCTV signal transmission over unshielded twisted pair wire (CAT 5 network cable)

Specifications

Video Input (BNC Connector)	1
Video Input	1V p-p, 75Ω
RJ-45 Output	Video Output
Transmission Distance	300m
Cable for RJ-45	CAT5 UTP
Temperature	Operation: 0°C to +55°C, Storage: -20°C TO 85°C, Humidity: up to 95%
Dimensions	69mm × 25mm × 20.7mm
Weight	30g

Part Number Table

Description	Part Number
BNC Male to RJ45 Female Video Transceiver	PSG08201

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet sheet sheet sheet sheet hendrom any the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands







Page <1>