



## Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

SN62 CRYSTAL 505 3C

SDS no. : 221841

V001.1

Revision: 23.11.2007

printing date: 14.05.2009

### 1. Identification of the substance/preparation and of the company/undertaking

**Trade name:**

SN62 CRYSTAL 505 3C

**Intended use:**

Solder Wire

**Company name:**

Henkel AG & Co. KGaA  
Henkelstr. 67  
40191 Düsseldorf

Germany

Phone: +49 (211) 797-0

**E-mail address of person responsible for Safety Data Sheet:**

ua-productsafety.uk@uk.henkel.com

**Emergency information:**

24 Hours Emergency Tel: +44 (0)20 8312 0291

### 2. Hazards identification

This product contains modified rosin.

Flux fumes emitted during reflow will irritate the nose and throat and may cause an asthmatic type reaction.

### 3. Composition / information on ingredients

**General chemical description:**

This is an article, according to EU Directives it does not require a Safety Data Sheet

**Declaration of ingredients according to EC/1907/2006:**

| Hazardous components<br>CAS-No. | EINECS<br>ELINCS | content   | Classification |
|---------------------------------|------------------|-----------|----------------|
| Tin<br>7440-31-5                | 231-141-8        | 60 - 80 % |                |
| Lead<br>7439-92-1               | 231-100-4        | 30 - 40 % |                |
| Silver<br>7440-22-4             | 231-131-3        | 1 - 5 %   |                |

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

### 4. First aid measures

**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.  
Obtain medical attention if irritation persists.

**Eye contact:**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Seek medical advice.

**Ingestion:**

Do not induce vomiting.  
Seek medical advice.

## 5. Fire fighting measures

**Combustion behaviour:**

The product itself does not burn. Any fire extinguishing action should be appropriate to the surroundings.

**Suitable extinguishing media:**

carbon dioxide, foam, powder  
fine water spray

**Special protection equipment for firefighters:**

Wear self-contained breathing apparatus.

**Hazardous combustion products:**

High temperatures may produce heavy metal dust, fumes or vapours., The flux medium will give rise to irritating fumes.

## 6. Accidental release measures

**Environmental precautions:**

Do not let product enter drains.

**Clean-up methods:**

Scrape up spilled material and place in a closed container for disposal.

## 7. Handling and storage

**Handling:**

Use only in well-ventilated areas.  
Avoid skin and eye contact.  
When using do not eat, drink or smoke.  
Wash hands before breaks and immediately after handling the product.

**Storage:**

Store in a cool place in closed original container.

## 8. Exposure controls / personal protection

### Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

| Ingredient                                   | ppm | mg/m <sup>3</sup> | Type                         | Category | Remarks       |
|--|-----|-------------------|------------------------------|----------|---------------|
| TIN (INORGANIC COMPOUNDS AS SN)<br>7440-31-5 |     | 2                 | Time Weighted Average (TWA). |          | EU-2000/39/EC |
| SILVER, METALLIC<br>7440-22-4                |     | 0,1               | Time Weighted Average (TWA). |          | EU-2000/39/EC |
|  |     | 0,1               | Time Weighted Average (TWA). |          | EH40 WEL      |
| Lead<br>7439-92-1                            |     | 0,15              | Time Weighted Average (TWA). |          | EH40 WEL      |
|  |     | 0,15              | Time Weighted Average (TWA). |          | EU_OEL        |
|  |     |                   |                              | Listed.  | EU_OEL_II     |
|  |     |                   | Biological Limit Value:      |          | EU_OEL_II     |

### Engineering controls:

Ensure adequate ventilation, especially in confined areas.

Extraction is necessary to remove fumes evolved during reflow.

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

### Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

### Eye protection:

Wear protective glasses.

## 9. Physical and chemical properties

### General characteristics:

Appearance solid

Odor: grey  
none

### Phys./chem. properties:

|  |                          |
|--|--------------------------|
| pH-value                               | not applicable           |
| Boiling point                          | Not determined           |
| Flash point                            | Not applicable           |
| Density                                | 8,5000 g/cm <sup>3</sup> |
| ( )                                    |                          |
| Solubility (qualitative)               | insoluble                |
| Melting point                          | 179,0 °C (354.2 °F)      |
| Octanol/Water distribution coefficient | Not determined           |
| VOC content                            | < 5,0 %                  |

## 10. Stability and reactivity

### Conditions to avoid:

Stable under normal conditions of storage and use.

**Materials to avoid:**

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides.  
Strong oxidizing agent.

**Hazardous decomposition products:**

Thermal decomposition can lead to release of irritating gases and vapors.

## 11. Toxicological information

**Oral toxicity:**

Harmful if swallowed.

**Inhalative toxicity:**

Fumes evolved at soldering temperatures will irritate the nose, throat and lungs. Prolonged or repeated exposure to flux fumes may result in sensitisation in sensitive workers.

**Skin irritation:**

Fumes emitted during soldering may irritate the skin.

**Eye irritation:**

Fumes emitted during soldering may irritate the eyes.

**Other remarks:**

Chronic overexposure to lead may result in damage to the blood forming, nervous, urinary and reproductive systems. Severe lead toxicity will cause sterility, abortion and neonatal mortality and morbidity.

## 12. Ecological information

**Mobility:**

No data available.

**Persistence and Biodegradability:**

The product is not biodegradable.

**Bioaccumulative potential:**

Octanol/Water distribution coefficient: Not determined

**General ecological information:**

Do not empty into drains / surface water / ground water.

## 13. Disposal considerations

**Product disposal:**

Wherever possible unwanted solder alloy should be recycled for recovery of metal.  
Otherwise dispose of in accordance with local and national regulations.

**Waste code(EWC):**

06 04 05 - wastes containing other heavy metals

**Disposal of uncleaned packages:**

Dispose of in accordance with local and national regulations.

## 14. Transport information

**General information:**

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

## 15. Regulations - classification and identification

### Indication of danger:

none

### Risk phrases:

No label

### Additional information:

Contains lead which may harm your health. Lead can cause birth defects and other reproductive harm.  
Regulations forbid the use of lead solder in any private or public drinking water supply system.  
Avoid breathing fumes given out during soldering.  
Flux fumes may irritate the nose, throat and lungs and may after prolonged/repeated exposure give an allergic reaction (asthma).  
After handling solder wash hands with soap and water before eating, drinking or smoking.  
Keep out of reach of children.

### National regulations/information (Great Britain):

#### Remarks

The Health & Safety at Work Act 1974.  
The Control of Substances Hazardous to Health Regulations. L5:General Approved Code of Practice to the COSHH Regulations. HS(G)97:A Step by Step Guide to the COSHH Regulations. HS(G)193: COSHH essentials: Easy steps to control chemicals.  
IND (G)248L:Solder fume and you. IND(G)249L:Controlling health risks from rosin (colophony) based solder fluxes.  
The Control of Lead at Work Regulations. L132:Control of Lead at Work: Approved Code of Practice and Guidance.  
Employees should be under medical surveillance if the risk assessment made under the Control of Lead at Work Regulations indicates they are likely to be exposed to significant concentrations of lead, or if an Employment Medical Advisor or appointed doctor so certifies.  
A woman employed on work which exposes her to lead should notify her employer as soon as possible if she becomes pregnant. The Employment Medical Advisor / Appointed Doctor should be informed of the pregnancy.  
Under the Management of Health and Safety at Work Regulations, employers are required to assess the particular risks to health at work of pregnant workers and workers who have recently given birth or who are breast feeding.

## 16. Other information

### Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.  
According to the regulations safety data sheet is not demanded for this product. This voluntary information is given in a format of 16 points.