

IE-PCB-SPM-P-180-SMD**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Single Pair Ethernet PCB sockets**

Single pair Ethernet is a technology that only requires one pair of wires to transmit data and power.

The resulting benefits will make SPE the preferred network at the field level and beyond.

Advantages of Single Pair Ethernet:

- Consistent: Single Pair Ethernet enables uniform Ethernet-based communication from the sensor to the cloud
- Future-proof: key technology for Industry 4.0 and IIoT
- Flexible: ranges of up to 1000 m and transmission properties of up to 1 Gbps enable use across applications
- Innovative: lighter, less space required, and reduced installation effort

General ordering data

Version	Built-in plugs, M8 PCB insert, IP67 with housing, SMD solder connection, 180°, Number of poles: 2
Order No.	2795110000
Type	IE-PCB-SPM-P-180-SMD
GTIN (EAN)	4064675 119166
Qty.	100 pc(s).

IE-PCB-SPM-P-180-SMD

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	14.5 mm	Depth (inches)	0.571 inch
Height	22.1 mm	Height (inches)	0.87 inch
Width	10.1 mm	Width (inches)	0.398 inch
Net weight	5.14 g		

Temperatures

Operating temperature	-40 °C...85 °C
-----------------------	----------------

System specifications

Category	T1-B	Mounting onto the PCB	SMD solder connection
Number of poles	2	Outgoing elbow	180°
Performance-Category	T1-B	Plugging cycles	≥ 100
Product family	Industrial Ethernet	Protection degree	IP67 with housing
Soldering process	Reflow soldering, Manual soldering		

Electrical properties

Insulation strength	≥ 500 MΩ	Rated current	4 A
Rated voltage	72 V		

Standards

Connector standard	IEC 63171-5
--------------------	-------------

Material data

Insulating material	LCP	Colour	black
Colour chart (similar)	RAL 9011	Insulation strength	≥ 500 MΩ
Moisture Level (MSL)	1	UL 94 flammability rating	V-0
Contact material	Copper alloy	Contact surface	Ni/Au
Operating temperature, min.	-40 °C	Operating temperature, max.	85 °C

Packing

VPE length	330 mm	VPE width	50.4 mm
VPE height	330 mm		

Classifications

ETIM 6.0	EC002637	ETIM 7.0	EC002637
ETIM 8.0	EC002637	ECLASS 9.0	27-44-04-02
ECLASS 9.1	27-44-04-02	ECLASS 10.0	27-44-04-02
ECLASS 11.0	27-46-02-01		

Approvals

ROHS	Conform
------	---------

IE-PCB-SPM-P-180-SMD

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Technical Documentation

[IE-PCB-SPM-P-180-SMD](#)

Catalogues

[Catalogues in PDF-format](#)