

IN-LINE FLOWMETERS FOR ULTRA-PURE WATER

FL-500UP Series
Starts at



Optional †

- ✓ Fluid is Always in Sight
- ✓ Direct-Reading English and Metric Scales
- ✓ Electro-Polished Version of Standard 316 SS Shaft and Spring Optionally Available
- ✓ PVDF End Fittings
- ✓ Polysulfone Body
- ✓ Perfluoroelastomer Seals
- ✓ Easily Mounted in Any Pipe Orientation

SPECIFICATIONS

Accuracy: ±5% FS
Pressure Drop: 4 psi at full scale flow
Maximum Pressure: 150 psig @ 20°C (68°F)
Maximum Temperature: 65°C (150°F) @ 0 psig
Dimensions: 177.8 mm (7") long,
 FL-505 through FL-515:
 50.8 mm (2") Dia.
 FL-530 through FL-550:
 76.2 mm (3") Dia.



Caution: Polysulfone should not be used in direct sunlight or any other significant sources of ultraviolet light.

FL-505UP, shown smaller than actual size.

The FL-500UP is a specialized meter for monitoring the flow rate of ultra-pure water to tools, on de-ionized water returns, and UPW returns. Also available are accessory switches for signaling specific flowrates. Each switch kit contains all the necessary hardware for quick and trouble-free mounting. Kits include a ring-shaped PTFE-coated ceramic magnet that fits around the float in the flowmeter, and a proximity switch mounted in a rugged housing that easily clamps to the body of the flowmeter. As the changing flow causes the float to move within the tube, the magnet moves with it, and its magnetic field trips the proximity switch at the predetermined flow rate. An adjustment screw allows for easy flow rate adjustment. Add 2 switches to indicate both high and low flow rate limits.

Note: Switch activates over a 25% FS band; above and below this band, the relay deactivates.

MOST POPULAR MODELS HIGHLIGHTED!

To Order (Specify Model Number)				
Model No.	Female NPT End Fittings	Dual Scales		
		GPM	LPM	
FL-505UP	1	0.5 to 5	2 to 20	
FL-510UP	1	1 to 10	4 to 38	
FL-515UP	1	1.5 to 15	6 to 55	
FL-520UP	1.5	2 to 20	8 to 75	
FL-530UP	1.5	3 to 30	11 to 110	
FL-540UP	1.5	4 to 40	15 to 150	
FL-550UP	1.5	5 to 50	20 to 200	

Accessory Switch Kits (Field Installable)

Model No.	For Sizes
FL-500-S1	FL-505, -510, -515
FL-500-S2	FL-520, -530, -540, -550
ES-2036	Reference Book: Handbook of Drinking Water Quality

Switch ratings: 8 W, 100 Vdc/120 Vac [at 25°C (77°F)]
 Comes complete with operator's manual.

† For NIST traceable certificate add suffix "-NIST" to model number.

For optional electro-polished 316 SS shaft and spring, add suffix "-EP" to model number and to price.

Ordering Examples: FL-505UP, 1" flowmeter, 0.5 to 5 GPM (2 to 20 LPM) range,
 FL-550UP, 1.5" flowmeter, 5 to 50 GPM (20 to 200 LPM) range,

omega.co.uk[®]

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

www.omega.co.uk



UNITED STATES

www.omega.com

1-800-TC-OMEGA
Stamford, CT.

UNITED KINGDOM

www.omega.co.uk

Manchester, England
0800-488-488
+44-(0)161-777-6611

CANADA

www.omega.ca

Laval(Quebec)
1-800-TC-OMEGA

FRANCE

www.omega.fr

0800-466-342

GERMANY

www.omega.de

Deckenfronn, Germany
0800-8266342

BENELUX

www.omega.nl

0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters