Normal Wall Tubing (2X)

Low Smoke, Halogen Free, Polyolefin, Heat Shrink

multicomp PRO

RoHS

Compliant



Description

Provides both commercial and military applications electrical insulation and protects in-line components, disconnect terminals and splices with its high strength and excellent resilience. Bundles wires for very flexible light-duty harnesses. Identifies or colour-codes wires, cables, terminals and components.

Specifications

Operating temperature	: -55°C to +135°C
Minimum Shrink temperature	: 70°C
Minimum Full recovery temperature	: 120°C
Shrink Ratio	: 2:1
Colours	: Red and Blue
Approvals	: UL224, 125°C 600V VW-1
Meets the AMS- DTL-23053/5 class	1&3
Resistant to common fluids and solv	/ents

Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D2671	≥10.4Mpa
Ultimate Elongation	ASTM D2671	≥200%
Longitudinal Shrinkage	UL 224	±5%
Heat Aging Tensile Strength Ultimate Elongation	158°C, 168hrs	≥7.3Mpa ≥100%
Heat shock	250°C, 4hrs	No cracking, No dripping
Dielectric Strength	ASTM D150	≥15kV/mm
Volume Resistivity	ASTM D2671	≥1x10¹⁴Ω·Cm
Copper Stability	UL224	Pass
Copper Corrosion	UL224	No corrosion

Product Dimensions

Part	Si	ze	As supplied	After Recovery	
Number	Inch	mm	Internal Diameter (mm)	Internal Diameter (mm)	Wall Thickness (mm)
PP001898	1/16	1.6	1.5 ±0.2	0.65	0.28 ±0.1
PP001907	1/10	1.0	1.5 ±0.2	0.05	0.20 ±0.1
PP001899	3/32	2.4	2.5 ±0.2	1	0.35 ±0.1
PP001908		2.4	2.3 ±0.2	I	0.35 ±0.1
PP001900	1/0	3.2	25,02	4.5	0.4.10.4
PP001909	1/8	3.2	3.5 ±0.2	1.5	0.4 ±0.1

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



Normal Wall Tubing (2X)

Low Smoke, Halogen Free, Polyolefin, Heat Shrink

Part	Size As suppli		As supplied	After Recovery	
Number	Inch	mm	Internal Diameter (mm)	Internal Diameter (mm)	Wall Thickness (mm)
PP001901	3/16	4.8	4.8 5 ±0.2	2.3	0.5 ±0.1
PP001910		4.0	5 ±0.2	2.5	0.5 ±0.1
PP001902	1/4	6.4	6.5 ±0.2	3	0.55 ±0.1
PP001911		0.4	0.5 ±0.2	5	0.55 ±0.1
PP001903	3/8	9.5	9.5 ±0.3	4.5	0.6 ±0.1
PP001912		9.5	9.5 ±0.5	4.5	0.0 ±0.1
PP001904	1/2	12.7	12.5 ±0.3	6	0.6 ±0.1
PP001913		12.7	12.5 ±0.5	0	0.0 ±0.1
PP001905	3/4	19	10 10 5	9	0.8 ±0.15
PP001914		19	19 ±0.5	9	0.0 ±0.15
PP001906	1	906 1 25.4 26 ±0.5	26 ±0.5	12.5	0.9 ±0.15
PP001915		20.4 20 ±0.5	12.5 0.9 ±0.	0.9 ±0.15	

Part Number Table

Description	Part Number
Tubing, Heat Shrink, 2:1, Boxed, 1.6mm, Red, 20m	PP001898
Tubing, Heat Shrink, 2:1, Boxed, 2.4mm, Red, 15m	PP001899
Tubing, Heat Shrink, 2:1, Boxed, 3.2mm, Red, 15m	PP001900
Tubing, Heat Shrink, 2:1, Boxed, 4.8mm, Red, 12m	PP001901
Tubing, Heat Shrink, 2:1, Boxed, 6.4mm, Red, 12m	PP001902
Tubing, Heat Shrink, 2:1, Boxed, 9.5mm, Red, 8m	PP001903
Tubing, Heat Shrink, 2:1, Boxed, 12.7mm, Red, 8m	PP001904
Tubing, Heat Shrink, 2:1, Boxed, 19mm, Red, 5m	PP001905
Tubing, Heat Shrink, 2:1, Boxed, 25.4mm, Red, 5m	PP001906
Tubing, Heat Shrink, 2:1, Boxed, 1.6mm, Blue, 20m	PP001907
Tubing, Heat Shrink, 2:1, Boxed, 2.4mm, Blue, 15m	PP001908
Tubing, Heat Shrink, 2:1, Boxed, 3.2mm, Blue, 15m	PP001909
Tubing, Heat Shrink, 2:1, Boxed, 4.8mm, Blue, 12m	PP001910
Tubing, Heat Shrink, 2:1, Boxed, 6.4mm, Blue, 12m	PP001911
Tubing, Heat Shrink, 2:1, Boxed, 9.5mm, Blue, 8m	PP001912
Tubing, Heat Shrink, 2:1, Boxed, 12.7mm, Blue, 8m	PP001913
Tubing, Heat Shrink, 2:1, Boxed, 19mm, Blue, 5m	PP001914
Tubing, Heat Shrink, 2:1, Boxed, 25.4mm, Blue, 5m	PP001915

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



multicomp PRO