

RoHS  
Compliant



## Features:

- Resin Coated, Heavy Weigth Braided Fiberglass won't burn melt or become brittle
- Minimal Dusting when cut & handled
- Cut & abrasion resistant
- Easy to install – cut with scissors
- Asbestos free
- Resists gasoline and engine chemicals

## Specifications:

Sleeving / Tubing Type : Insulating  
Length : 30.5m  
Sleeving Material : Fibreglass  
Internal Diameter : 12.7mm  
Sleeving Colour : Black  
Use With : Cable & Wire

## Physical Properties:

Wall Thickness : 0.085  
Abrasion Resistance : Med.

## Operating Temperatures:

Min. Continuous : -70°C / -94°F  
Max. Continuous : 650°C / 1202°F  
Melt : 1,120°C / 2,048°F

## Chemical Resistance

Agent	Effect
Aliphatic Solvents	1
Chlorinated Solvents	1
Weak Bases	1
Salts	1
Salt Water	1
Hydraulic Fluid	1
Lube Oil	1
De-Icing Fluid	1
Strong Oxidants	2
Esters / Keytones	1
UV Light	2
Petroleum	1
Fungus	1

1. No Effect
2. Little Effect
3. Moderate Effect
4. Greater Effect
5. Severe Effect

## Notes:

Hi-Temp, resin coated sleeving is an extremely high temperature resistant sleeve commonly used as thermal protection for wires, cables and hoses that are subjected to continuous and extreme high temperature environments, such as engine manifolds and exhaust systems. It installs easily over a variety of applications to either deflect or retain heat in environments up to 1,200°F

Braided from fibreglass yarns and coated with high temperature resins, making it tough and durable, maintaining its tight structure under extreme vibration, abrasion, mechanical stress and temperature variations.

## Part Number Table

Description	Nominal Size (Inches)	Maximum Dia (Inches)	Wall Thickness (Inches)	Spool Length	Part Number
Hi-Temp Resin Coated Fiberglass Sleeving	1/4	1/2	0.043	100	SPC14520
	3/8	5/8	0.043	100	SPC14521
	1/2	3/4	0.046	100	SPC14522
	5/8	7/8	0.046	50	SPC14523
	3/4	1-1/8	0.046	50	SPC14524
	7/8	1-1/4	0.046	50	SPC14525
	1	1-5/8	0.057	25	SPC14526

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.