



## AZM201Z-ST-T-1P2PW-2965-1-DU

- Thermoplastic enclosure
- Max. length of the sensor chain 200 m
- Self-monitoring series-wiring
- Coding in accordance to ISO 14119 by using RFID-Technology
- 3 LEDs to show operating conditions
- Sensor technology permits an offset between actuator and interlock of  $\pm 5$  mm vertically and  $\pm 3$  mm horizontally
- Suitable for hinged and sliding guards
- Intelligent diagnosis
- Manual release
- Protection class IP66, IP67
- High holding force 2000
- symmetrical construction form, assembly on 40mm profiles
- OSSD safety outputs
- Emergency exit / Emergency release suitable for retrofitting

## Data

### Ordering data

|                               |                              |
|-------------------------------|------------------------------|
| Product type description      | AZM201Z-ST-T-1P2PW-2965-1-DU |
| Article number (order number) | 103044810                    |
| EAN (European Article Number) | 4030661563824                |
| eCl@ss number, version 12.0   | 27-27-26-03                  |
| eCl@ss number, version 11.0   | 27-27-26-03                  |
| eCl@ss number, version 9.0    | 27-27-26-03                  |
| ETIM number, version 7.0      | EC002593                     |
| ETIM number, version 6.0      | EC002593                     |

### Approvals - Standards

|              |                                  |
|--------------|----------------------------------|
| Certificates | TÜV<br>cULus<br>EAC<br>FCC<br>IC |
|--------------|----------------------------------|

## General data

|  |  |
|--|--|
| Standards  | EN IEC 62061<br>EN ISO 13849-1<br>EN ISO 14119<br>EN IEC 60947-5-1<br>EN IEC 60947-5-3<br>EN IEC 61508 |
| Coding   | Universal coding   |
| Coding level according to EN ISO 14119                                 | Low  |
| Working principle  | RFID   |
| Enclosure material   | Glass-fibre, reinforced thermoplastic  |
| Gross weight   | 508 g  |
| Time to readiness, maximum   | 4,000 ms   |
| Duration of risk, maximum  | 200 ms   |
| Reaction time, switching off safety outputs via actuator, maximum      | 100 ms   |
| Reaction time, switching off safety outputs via safety inputs, maximum | 0.5 ms   |

## General data - Features

|                              |     |
|------------------------------|-----|
| Power to unlock              | Yes |
| Solenoid interlock monitored | Yes |
| Manual release               | Yes |
| Short circuit detection      | Yes |
| Cross-circuit detection      | Yes |
| Series-wiring                | Yes |
| Idle assignable pushbutton   | Yes |
| Freely assignable LED        | Yes |

|                                     |     |
|-------------------------------------|-----|
| Safety functions                    | Yes |
| Integral system diagnostics, status | Yes |
| Number of safety contacts           | 2   |

### Safety classification

|           |  |
|-----------|--|
| Standards | EN ISO 13849-1<br>EN IEC 62061<br>EN IEC 61508 |
|-----------|--|

### Safety classification - Interlocking function

|  |                          |
|--|--------------------------|
| Performance Level, up to                                   | e                        |
| Category   | 4                        |
| PFH value  | $1.90 \times 10^{-9}$ /h |
| PFD value  | $1.60 \times 10^{-4}$    |
| Safety Integrity Level (SIL), suitable for applications in | 3                        |
| Mission time   | 20 Year(s)               |

### Safety classification - Guard locking function

|  |                          |
|--|--------------------------|
| Performance Level, up to                                   | d                        |
| Category   | 2                        |
| PFH value  | $1.00 \times 10^{-8}$ /h |
| PFD value  | $8.90 \times 10^{-4}$    |
| Safety Integrity Level (SIL), suitable for applications in | 2                        |
| Mission time   | 20 Year(s)               |

### Mechanical data

|  |                      |
|--|----------------------|
| Mechanical life, minimum                               | 1,000,000 Operations |
| Holding force $F_{Zh}$ in accordance with EN ISO 14119 | 2,000 N              |

|                                    |         |
|------------------------------------|---------|
| Holding force $F_{\max}$ , maximum | 2,600 N |
| Latching force                     | 30 N    |
| Actuating speed, maximum           | 0.2 m/s |

### Mechanical data - Connection technique

|             |                        |
|-------------|------------------------|
| Termination | Connector M23, 12-pole |
|-------------|------------------------|

### Mechanical data - Dimensions

|                  |        |
|------------------|--------|
| Length of sensor | 50 mm  |
| Width of sensor  | 40 mm  |
| Height of sensor | 220 mm |

### Ambient conditions

|  |                                  |
|--|----------------------------------|
| Degree of protection                       | IP67<br>IP66                     |
| Ambient temperature, minimum               | -25 °C                           |
| Ambient temperature, maximum               | +60 °C                           |
| Storage and transport temperature, minimum | -25 °C                           |
| Storage and transport temperature, maximum | +85 °C                           |
| Relative humidity, minimum                 | 30 %                             |
| Relative humidity, maximum                 | 95 %                             |
| Note (Relative humidity)                   | non-condensing                   |
| Resistance to vibration to EN 60068-2-6    | 10 ... 150 Hz, amplitude 0.35 mm |
| Resistance to shock                        | 30 g / 11 ms                     |
| Protection class                           | III                              |

### Ambient conditions - Insulation values

|                                |        |
|--------------------------------|--------|
| Rated insulation voltage $U_i$ | 32 VDC |
|--------------------------------|--------|

|  |        |
|--|--------|
| Rated impulse withstand voltage<br>$U_{imp}$ | 0.8 kV |
| Overvoltage category                         | III    |
| Degree of pollution to VDE 0100              | 3      |

### Electrical data

|  |                 |
|--|-----------------|
| Operating voltage, minimum                     | 20.4 VDC        |
| Operating voltage, maximum                     | 26.4 VDC        |
| No-load supply current $I_0$ ,<br>maximum      | 50 mA           |
| Current consumption with magnet<br>ON, average | 200 mA          |
| Current consumption with magnet<br>ON, peak    | 700 mA / 100 ms |
| Operating current                              | 1,200 mA        |
| Switching frequency, approx.                   | 1 Hz            |

### Electrical data - Magnet control

|                                   |  |
|-----------------------------------|--|
| Switching thresholds              | -3 V ... 5 V (Low)<br>15 V ... 30 V (High) |
| Classification ZVEI CB24I, Sink   | C0   |
| Classification ZVEI CB24I, Source | C1<br>C2<br>C3                             |

### Electrical data - Safety digital inputs

|                                   |  |
|-----------------------------------|--|
| Switching thresholds              | -3 V ... 5 V (Low)<br>15 V ... 30 V (High) |
| Classification ZVEI CB24I, Sink   | C1   |
| Classification ZVEI CB24I, Source | C1<br>C2<br>C3                             |

### Electrical data - Safety digital outputs

|  |          |
|--|----------|
| Rated operating current (safety outputs) | 250 mA   |
| Voltage drop $U_d$ , maximum             | 2 V      |
| Leakage current $I_r$ , maximum          | 0.5 mA   |
| Voltage, Utilisation category DC-13      | 24 VDC   |
| Current, Utilisation category DC-13      | 0.25 A   |
| Classification ZVEI CB24I, Source        | C2       |
| Classification ZVEI CB24I, Sink          | C1<br>C2 |

### Electrical data - Diagnostic outputs

|                                     |        |
|-------------------------------------|--------|
| Operating current                   | 50 mA  |
| Voltage drop $U_d$ , maximum        | 4 V    |
| Voltage, Utilisation category DC-13 | 24 VDC |
| Current, Utilisation category DC-13 | 0.05 A |

### Status indication

|   |  |
|---|--|
| Note (LED switching conditions display) | Operating condition: LED green<br>Error / functional defect: LED red<br>Supply voltage UB: LED green |
|---|--|

### Pin assignment

|       |                       |
|-------|-----------------------|
| PIN 1 | A1 Supply voltage UB  |
| PIN 2 | X1 Safety input 1     |
| PIN 3 | A2 GND                |
| PIN 4 | Y1 Safety output 1    |
| PIN 5 | OUT Diagnostic output |
| PIN 6 | X2 Safety input 2     |
| PIN 7 | Y2 Safety output 2    |
| PIN 8 | IN Solenoid control   |

|        |            |
|--------|------------|
| PIN 9  | white LED  |
| PIN 10 | Key button |
| PIN 11 | Key button |
| PIN 12 | Not used   |

## Scope of delivery

|                   |   |
|-------------------|---|
| Scope of delivery | Actuators must be ordered separately.<br>Triangular key for AZM 201 |
|-------------------|---|

## Accessory

|                           |                               |
|---------------------------|-------------------------------|
| Recommendation (actuator) | AZ/AZM201-B1<br>AZ/AZM201-B30 |
|---------------------------|-------------------------------|

## Note

|                |  |
|----------------|--|
| Note (General) | As long as the actuating unit remains inserted in the solenoid interlock, the unlocked safety guard can be relocked. In this case, the safety outputs are re-enabled, so that the safety guard must not be opened. |
|----------------|--|

## Ordering code

Product type description:  
AZM201(1)-(2)-(3)-T-(4)-(5)

|                |  |
|----------------|--|
| (1)            |  |
| <b>Z</b>       | Solenoid interlock monitored           |
| <b>B</b>       | Actuator monitored                     |
| (2)            |  |
| <b>without</b> | Standard coding                        |
| <b>I1</b>      | Individual coding                      |
| <b>I2</b>      | Individual coding, re-teaching enabled |
| (3)            |  |
| <b>SK</b>      | Screw terminals                        |

|                |  |
|----------------|--|
| <b>CC</b>      | Cage clamps  |
| <b>ST2</b>     | Connector plug M12, 8-pole   |
| (4)            |  |
| <b>1P2PW</b>   | 1 diagnostic output, p-type and >2 safety outputs, p-type > (combined diagnostic signal: guard system closed and interlock locked) |
| <b>SD2P</b>    | serial diagnostic output and 2 p-type safety outputs   |
| (5)            |  |
| <b>without</b> | Power to unlock  |
| <b>A</b>       | Power to lock  |


## Pictures

### Product picture (catalogue individual photo)



ID: kazm2f28  
 | 993.8 kB | .jpg | 177.447 x 833.261 mm - 503 x 2362 px - 72 dpi  
 | 276.4 kB | .png | 74.083 x 347.839 mm - 210 x 986 px - 72 dpi  
 | 10.6 kB | .jpg | 42.686 x 200.025 mm - 121 x 567 px - 72 dpi

### Dimensional drawing basic component



ID: 1azm2g12  
 | 146.3 kB | .jpg | 352.778 x 308.681 mm - 1000 x 875 px - 72 dpi  
 | 5.3 kB | .png | 74.083 x 64.911 mm - 210 x 184 px - 72 dpi  
 | 21.1 kB | .jpg | 169.686 x 148.519 mm - 481 x 421 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 30/09/2022, 06:46