Type A Plug to Type A Receptacle

pro-signal



Specifications

Connector to Connector : Type A Plug to Type A Receptacle


USB Standard : USB 3.0 Contact Resistance : 2Ω Max.

Insulation Resistance : DC 300V/10ms, $10M\Omega$ Min.

Cable Length : 1m (3.28ft)

Jacket Colour : Black

Diagram



Conn. 1 Pin Assignment Conn. 2
$\begin{array}{c} 1 \\ 2 \\ 3 \end{array} \qquad \begin{array}{c} 1 \\ 2 \\ 3 \end{array}$
$\begin{array}{c} 4 \\ 5 \\ 6 \end{array}$
7 7 8 8 9 9 9
Shell Shield Shell

No	Description	Qty.	Unit
1	USB 3.0~UL2725~[28AWG×(7/0.127TC)+EAM]×2P+[28AWG×(7/0.127TC)+A] ×1P+28AWG(7/0.127TC)×2C+AEB (16/5/0.12AL 65% AL) OD:5.5mm Black	1	m
2	USB 3.0 A (M) 9P Connector	1	PC
3	USB 3.0 A (M) Tin plate		
4	USB 3.0 A (M) Tin plate		
5	USB 3.0 AF 9 Pin Connector		
6	45P Black PVC	20	g
7	USB 3.0 A (M) Tee Connector	1	PC
8	USB 3.0 AF Tee Connector		
9	Heat Shrinkable Casing	0.013	m
10	PE Low density	5	g

Part Number Table

Description	Part Number
Type A Plug to Type A Receptacle, Black, 1m	CAC250043

Dimensions: Millimetres

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

