

Product Search Data Sheet

Note: This datasheet may be out of date. ${\it Please download the latest datasheet of DE2E3SA472MN3AT02F from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DE2E3SA472MN3AT02F

DE2E3SA472MN3AT02F


















Appearance & Shape









References

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| A | Ammo Pack | 1000 |

| Mass (typ.) | |
|-------------|-------|
| 1 piece | 0.66g |



Notices

X1/Y2 Class Certified Products、 Halogen-free Products、 Rated Voltage X1:300Vac(r.m. s.)/Y2:250Vac(r.m.s.)/1kVdc

1 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: This datasheet may be out of date. ${\it Please download the latest datasheet of DE2E3SA472MN3AT02F from the official website of Murata}$ Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DE2E3SA472MN3AT02F

DE2E3SA472MN3AT02F



Specifications

| L size or Outer diameter D | 10.000000000000000000000000000000000000 | |
|-----------------------------|---|--|
| L size of Outer diameter D | 10.0mm max. | |
| T size | 5.0mm max. | |
| Lead spacing F | 7.5±1.0mm | |
| Lead diameter d | 0.6±0.05mm | |
| Paint dripping e | Up to the end of crimp | |
| Capacitance | 4700pF ±20% | |
| Rated voltage | 250Vac(r.m.s.) | |
| Temperature characteristics | E(JIS) | |
| Capacitance change rate | +20/-55% | |
| Temperature range of | -25°C to 85°C | |
| temperature characteristics | -23 € 10 03 € | |
| Operating Temperature | -40°C to 125°C | |
| Range | | |

2 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of DE2E3SA472MN3AT02F from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=DE2E3SA472MN3AT02F


DE2E3SA472MN3AT02F





Characteristic Data

The charts below may show another part number which shares its characteristics.









3 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of DE2E3SA472MN3AT02F from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=DE2E3SA472MN3AT02F

DE2E3SA472MN3AT02F



DE2E3SA472MN3ATO2F C-Temp. capchange, DCOV,



DE2E3SA472MN3ATO2F S21 DCOV,2OdegC

4 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

