



MODEL 44004

Precision Epoxy NTC Thermistor

- 2252 ohm Resistance @ 25°C
- Interchangeable $\pm 0.2^{\circ}\text{C}$, 0°C to 70°C
- Pressed Disk Ceramic Sensor
- High sensitivity
- Thermally conductive epoxy coating
- 0.095" (2.4 mm) Maximum Diameter
- 32 AWG, 3" (7.6 cm) long Silver plated copper leads
- RoHS Compliant

FEATURES

- 2252 Ohm Resistance @ 25°C
- Interchangeability
- Good Long Term Stability
- High Sensitivity
- Thermally Conductive Epoxy Coating
- RoHS Compliance

APPLICATIONS

- High-range Temperature Applications
- Tight Tolerance Instrumentation
- General Applications Requiring Stability
- Applications Requiring Sensing Small Changes in Temperature
- Non-condensing Moisture Environments
- Allows use in Applications World-wide


MODEL 44004

Precision Epoxy NTC Thermistor

PERFORMANCE SPECS

Parameter	Units	Value
Resistance @ 25°C	Ohms	2252
Tolerance 0°C to 70°C	°C	± 0.2
Beta Value 25/85	K	3978
Tolerance on Beta Value	%	0.8
Time response in air	Seconds	< 10
Dissipation Constant in air	mW/°C	1
Insulation Resistance (Min. of 100 Mohms for 1 sec.)	Volts	500

MECHANICAL DETAILS



TYPICAL PERFORMANCE CURVES (RESISTANCE OF INDIVIDUAL THERMISTORS)

Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms
-55	217.100	-14	15.540	27	2.064	68	0.4225	109	0.1182
-54	201.700	-13	14.700	28	1.977	69	0.4082	110	0.1150
-53	187.400	-12	13.910	29	1.894	70	0.3945	111	0.1118
-52	174.300	-11	13.160	30	1.815	71	0.3812	112	0.1088
-51	162.200	-10	12.460	31	1.739	72	0.3685	113	0.1058
-50	151.000	-9	11.810	32	1.667	73	0.3562	114	0.1030
-49	140.600	-8	11.190	33	1.599	74	0.3445	115	0.1002
-48	131.000	-7	10.600	34	1.533	75	0.3331	116	0.0976
-47	122.100	-6	10.050	35	1.471	76	0.3223	117	0.0950
-46	113.900	-5	9.534	36	1.412	77	0.3118	118	0.0925
-45	106.300	-4	9.046	37	1.355	78	0.3017	119	0.0900
-44	99.260	-3	8.586	38	1.301	79	0.2920	120	0.0877
-43	92.720	-2	8.151	39	1.249	80	0.2827	121	0.0854
-42	86.650	-1	7.741	40	1.200	81	0.2737	122	0.0832
-41	81.020	0	7.355	41	1.152	82	0.2650	123	0.0811
-40	75.790	1	6.989	42	1.107	83	0.2567	124	0.0790
-39	70.930	2	6.644	43	1.064	84	0.2486	125	0.0770
-38	66.410	3	6.319	44	1.023	85	0.2409	126	0.0750
-37	62.210	4	6.011	45	0.9838	86	0.2334	127	0.0731
-36	58.300	5	5.719	46	0.9462	87	0.2262	128	0.0713
-35	54.660	6	5.444	47	0.9102	88	0.2193	129	0.0695
-34	51.270	7	5.183	48	0.8758	89	0.2126	130	0.0678
-33	48.110	8	4.937	49	0.8428	90	0.2061	131	0.0661
-32	45.170	9	4.703	50	0.8113	91	0.1999	132	0.0644
-31	42.420	10	4.482	51	0.7811	92	0.1939	133	0.0629
-30	39.860	11	4.273	52	0.7522	93	0.1881	134	0.0613
-29	37.470	12	4.074	53	0.7245	94	0.1825	135	0.0598
-28	35.240	13	3.886	54	0.6979	95	0.1771	136	0.0584
-27	33.150	14	3.708	55	0.6725	96	0.1719	137	0.0570
-26	31.200	15	3.539	56	0.6481	97	0.1669	138	0.0556
-25	29.380	16	3.378	57	0.6248	98	0.1620	139	0.0543
-24	27.670	17	3.226	58	0.6024	99	0.1573	140	0.0530
-23	26.070	18	3.081	59	0.5809	100	0.1528	141	0.0517
-22	24.580	19	2.944	60	0.5603	101	0.1484	142	0.0505
-21	23.180	20	2.814	61	0.5405	102	0.1442	143	0.0493
-20	21.870	21	2.690	62	0.5215	103	0.1401	144	0.0482
-19	20.640	22	2.572	63	0.5033	104	0.1361	145	0.0470
-18	19.480	23	2.460	64	0.4858	105	0.1323	146	0.0459
-17	18.400	24	2.354	65	0.4690	106	0.1286	147	0.0449
-16	17.390	25	2.252	66	0.4529	107	0.1250	148	0.0438
-15	16.430	26	2.156	67	0.4374	108	0.1216	149	0.0428
								150	0.0418

MODEL 44004

Precision Epoxy NTC Thermistor

ORDERING INFORMATION

Part Number	Description	Ω @25°C	MOQ
701004	44004RC, THERMISTOR, ROHS COMPLIANT	2252	300
701104	44004RC-BP (100 PCS), THERM, ROHS	2252	300

* For quantities less than Minimum Order Quantity – contact distribution

NORTH AMERICA

Measurement Specialties, Inc.,
a TE Connectivity Company
Tel: 800-522-6752
customercare.ando@te.com

EUROPE

Measurement Specialties (Europe), Ltd.,
a TE Connectivity Company
Tel: 800-440-5100
customercare.tlse@te.com

ASIA

Measurement Specialties (China), Ltd.,
a TE Connectivity Company
Tel: 0400-820-6015
customercare.chdu@te.com

te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties (MEAS), American Sensor Technologies (AST), TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.