

# Stellaris® Serial-to-Ethernet Module and Reference Design Kit



LUMINARY MICRO

The tiny-footprint Luminary Micro Stellaris® Serial-to-Ethernet Module (MDL-S2E) offers a complete, ready-to-implement solution designed to add Ethernet connectivity to any serial device. The most common application for the MDL-S2E is for augmenting legacy products that contain a serial port for a configuration or control interface. Simply installing a Stellaris® Serial-to-Ethernet Module into the legacy serial device provides instant networking capability with no major board redesign or software changes, a tiny form-factor for unobtrusive implementation, and cable lengths much longer than what is available for simple serial connections.

## Features

The MDL-S2E is the first serial-to-Ethernet converter available with a highly integrated ARM® Cortex™-M3 microcontroller with 50 MHz of performance and ample single-cycle, on-chip Flash and SRAM memory for efficient network traffic handling. The MDL-S2E is ready out-of-the-box for immediate integration in a system, and software source files are included for complete customization.



The MDL-S2E ships as a ready-for-production module with the following features:

- Stellaris® LM3S6432 ARM® Cortex™-M3 microcontroller in a 10 x 10 mm BGA package for reduced board size
- 10/100 Mbit Ethernet port
  - Auto MDI/MDIX cross-over correction
  - Traffic and link indicators
- Two serial ports, configured as DCE, include RTS/CTS for flow control
  - RS-232 level available with UART0 with communication up to 230,400 baud
  - CMOS/TTL levels available with UART1 with communication up to 1 Mbaud
- Program firmware updates over Ethernet

- Module software
  - IP configuration with static IP address or DHCP
  - Raw and Telnet protocol support for access to serial port
  - Telnet client for Ethernet-based serial port extender
  - Web server for module configuration
  - Universal Plug and Play (UPnP) for device discovery
- Windows utility software
  - S2ECONF configuration application
- Module supports 5 V and 3.3 V supplies
- Flexible mounting options

## Kit Contents



The Stellaris® Serial-to-Ethernet Module is offered as a stand-alone, ready-for-production module (MDL-S2E) and also as a reference design kit (RDK-S2E). The RDK ships with everything needed to quickly evaluate and easily customize the MDL-S2E for your specific application, including:

- Stellaris® Serial-to-Ethernet Module (MDL-S2E)
- RS-232 adaptor board
- Retractable Ethernet cable
- DB9 serial cable
- USB cable for module power
- JTAG/SWD adapter to standard 20-pin header
- Quickstart Guide, User's Manual, Software Reference Manual, Board Data Sheet, source code, BOM, schematics, and Gerber files on CD

## Ordering Information

Product Number	Description
MDL-S2E	Stellaris® Serial-to-Ethernet Module for Single-Unit Packaging
MDL-S2E-B	Stellaris® Serial-to-Ethernet Module for Volume Packaging
RDK-S2E	Stellaris® Serial-to-Ethernet Reference Design Kit

Luminary Micro, Inc. • 108 Wild Basin, Suite 350 • Austin, TX 78746  
Main: +1-512-279-8800 • Fax: +1-512-279-8879 • <http://www.luminarymicro.com> • [sales@luminarymicro.com](mailto:sales@luminarymicro.com)

Copyright © 2008 Luminary Micro, Inc. All rights reserved. Stellaris, Luminary Micro, and the Luminary Micro logo are registered trademarks of Luminary Micro, Inc. or its subsidiaries in the United States and other countries. ARM and Thumb are registered trademarks, and Cortex is a trademark of ARM Limited. Other names and brands may be claimed as the property of others.



LUMINARY MICRO



Intelligent Processors by ARM