



## Mounting and Coupling Hardware

(K)  
(KM)




**Jackscrew Assembly  
High Profile**  
(K) 096-0002-0010  
**M83513/5-06**  
(KM) 096-0002-0084

(L)  
(LM)




**Jackscrew Assembly  
Low Profile**  
(L) 096-0002-0011  
**M83513/5-05**  
(LM) 096-0002-0085

(P)




**Jackpost Assembly**  
(P) 096-0002-0009  
**M83513/5-07**  
P mates with K,KM, L,LM, Q,QM  
and R,RM Jackscrew Assemblies.

(Q)  
(QM)




**Jackscrew Assembly  
High Profile**  
(Q) 096-0002-0014  
**M83513/5-03**  
(QM) 096-0002-0086

(R)  
(RM)




**Jackscrew Assembly  
Low Profile**  
(R) 096-0002-0015  
**M83513/5-02**  
(RM) 096-0002-0087

(H)  
(HM)



**Jackscrew Assembly  
High Profile**  
(H) 096-0002-0061  
**M83513/5-16**  
(HM) 096-0002-0088

(J)  
(JM)



**Jackscrew Assembly  
Low Profile**  
(J) 096-0002-0062  
**M83513/5-15**  
(JM) 096-0002-0089

(T)

(N)

(S)

### Notes:

1. Jackpost Assemblies will accommodate 3/32" max. thickness panel.
2. Letter(s) in parentheses is to assist in ordering hardware with the connector (See "How To Specify" page 7).
3. Single letters (e.g. K) designate hardware that meets M83513/5 requirements except the material is 303 stainless steel, passivated.
4. Add M suffix (e.g. KM) to designate hardware that meets all M83513/5 requirements. Material is corrosion resistant steel, non-magnetic, 125,000 PSI tensile strength minimum (Applies to jackscrews only).
5. Hardware ordered separately should be ordered in pairs; i.e. 2 pcs. P/N 096-0002-0009 per connector half.
6. Items in bold italic are qualified to MIL-PRF-83513.


MICRODOT

# Microminiature D Connectors

## Mounting and Coupling Hardware (Continued)


For Screw Mount MCK,  
MCD and MCDM (Continued)

Slot Head  
(X)



**Lockscrew Assembly**  
096-0002-0008


1/16" Allen Head  
(Y)



**Lockscrew Assembly**  
096-0002-0013

For Clip Mount — MCD


(Z)



**Mounting Key and Clip**  
P/N 096-0001-0000  
(2 Required)

For Float Mount — MCK,  
MCD and MCDM

(F)



**Float Mount Bushing**  
(Factory Installed)