

## AMP | Heavy Duty Sealed Connector Series

TE Internal #: 2-2366768-1

Housing for Female Terminals, Wire-to-Wire, 4 Position, .098 in [2.5] mm] Centerline, Sealable, Gray, Signal, -104 – 284 °F [-40 – 140 °C],

Key B

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Heavy Duty Sealed Connector Series Housings











Connector & Housing Type: Housing for Female Terminals

Mating Tab Width: 1.2 mm [ .047 in ] Connector System: Wire-to-Wire

Number of Positions: 4

Centerline (Pitch): 2.5 mm [ .098 in ]

All Heavy Duty Sealed Connector Series Housings (204)

# **Features**

## **Product Type Features**

Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Hybrid Connector	No
Primary Locking Feature	Clean Body
Configuration Features	
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Nominal Voltage Architecture	32 V



Primary Product Color	Gray
Connector & Keying Code	В
Contact Features	
Contact Type	Receptacle
Mating Tab Width	1.2 mm[.047 in]
Contact Current Rating (Max)	16 A
Housing Features	
Centerline (Pitch)	2.5 mm[.098 in]
Usage Conditions	
Operating Temperature (Max)	140 °C[284 °F]
Operating Temperature Range	-40 - 140 °C[-104 - 284 °F]
Operation/Application	
Circuit Application	Signal
Other	
Connector Position Assurance Capable	Yes

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts











# Also in the Series | Heavy Duty Sealed Connector Series



Automotive Connector Caps & Covers (25)



Automotive Housings(207)



Automotive Seals & Cavity Plugs(5)



Data Connectivity Headers(2)



Data Connectivity Housings(18)



Other Automotive Connector Accessories(34)



PCB Headers & Receptacles(1)

## **Documents**

**Product Drawings** 



### 4POS,MCON 1.2,REC HSG ASSY,COD B

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-2366768-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2366768-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2366768-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English