

Thermal printer ribbons for

Heatshrink and Tiptags


The thermal transfer print technology is based on heating up certain dots in the print head. This transfers the ink very precisely from the ribbon onto the surface of the printed material. All HellermannTyton ribbons consist of a special resin composition to maximise print performance. In combination with HellermannTyton printers the ribbons ensure the highest of print quality on all HellermannTyton thermal printable identification materials.

Features and benefits

- Thermal transfer ribbons for high quality print results on heat shrink tubing and Tiptag identification tags
- Ribbons are specifically designed to maximize print performance for the recommended material



Ribbons for printing on tubes and Tiptags.



ID: The standard inside core diameter is 25.4 mm.

TYPE	Recommended Material	Colour	Width (W)	Reel Length	Article-No.
TTRHTBK 70MM	TAGPU	Black (BK)	70.0	300 m	556-00204
TTRHTBK 100MM	TAGPU	Black (BK)	100.0	300 m	556-00210
TTRHTWH 70MM	TAGPU	White (WH)	70.0	300 m	556-00209
TTRHTWH 100MM	TAGPU	White (WH)	100.0	300 m	556-00211
TT822OUT8 110MM	TCGT/TULT	Silver (SR)	110.0	300 m	556-00161
TTDTHOUT 40MM	TCGT/TULT/TLFX/TLFD/TIPTAG	Black (BK)	40.0	300 m	556-00139
TTDTHOUT 60MM	TCGT/TULT/TLFX/TLFD/TIPTAG	Black (BK)	60.0	300 m	556-00140
TTDTHOUT 100MM	TCGT/TULT/TLFX/TLFD/TIPTAG	Black (BK)	100.0	300 m	556-00141
TTRW 30MM	TCGT/TULT/TTAGMC	White (WH)	30.0	300 m	556-00125
TTRW 60MM	TCGT/TULT/TTAGMC	White (WH)	60.0	300 m	556-00137
TTRC+ 30MM	TIPTAG PU/TAGPU	Black (BK)	30.0	300 m	556-00114
TTRC+ 60MM	TIPTAG PU/TAGPU	Black (BK)	60.0	300 m	556-00115
TTRC+ 100MM	TIPTAG PU/TAGPU	Black (BK)	100.0	300 m	556-00103

All dimensions in mm. Subject to technical changes.

