


Data Sheet | Item Number: 787-1011

Switched-mode power supply; Compact; 1-phase; 12 VDC output voltage; 4 A output current

<https://www.wago.com/787-1011>



Features:

- Switched-mode power supply
- Natural convection cooling when horizontally mounted
- Stepped profile, ideal for distribution boards/boxes
- Overhead mounting is possible with derating
- Suitable for both parallel and series operation
- Electrically isolated output voltage (SELV) per EN 61010-2-201/UL 60950-1; PELV per EN 60204

Technical data

Input		Output	
Phases	1	Nominal output voltage $U_{o, \text{nom}}$	DC 12 V (SELV)
Nominal input voltage $U_{i, \text{nom}}$	1 x AC 100 ... 240 V	Output voltage range	DC 10.5 ... 15.5 V (adjustable)
Input voltage range	1 x AC 85 ... 264 V; DC 120 ... 300 V	Default setting	DC 12 V
Input voltage derating	$I_o \leq 3.5 \text{ A}$ (< 100 VAC)	Nominal output current $I_{o, \text{nom}}$	4 A (12 VDC); 2.4 A (in any mounting position)
Nominal mains frequency range	44 ... 66 Hz; 0 Hz	Nominal output power	48 W
Input current I_i	$\leq 0.5 \text{ A}$ (230 VAC); $\leq 0.9 \text{ A}$ (110 VAC)	Deviation	$\leq 2 \%$
Discharge current	$\leq 1 \text{ mA}$	Residual ripple	$\leq 100 \text{ mV}$ (peak-to-peak)
Inrush current	$\leq 30 \text{ A}$ (NTC)	Current limitation	$1.1 \times I_{o, \text{nom}}$ (typ.)
Power factor correction (PFC)	passive	Overload behavior	Constant current
Mains failure hold-up time	$\geq 80 \text{ ms}$ (230 VAC); $\geq 10 \text{ ms}$ (110 VAC)		

Signaling and communication

Signaling	1 x Status indication LED (green)
Operation status indicator	Green LED (U_o)

Efficiency/power losses

Power loss P_I	$\leq 2.2 \text{ W}$; $\leq 8.5 \text{ W}$ (230 VAC; nominal load)
Power loss (max.) $P_{I(\text{max})}$	9 W (100 VAC / 12 VDC; 4 A)
Efficiency (typ.)	85 %

Circuit protection

Internal fuse	T 2 A / 250 VAC
Backup fusing (required)	An external DC fuse is required for the DC input voltage.
Backup fusing (recommended)	Circuit breaker: 6 A (C characteristic), 10 A (B characteristic) or higher

Safety and protection

Isolation voltage (pri.-sec.)	DC 4.242 kV
Protection class	II
Protection type	IP20; per EN 60529
Resistance to reverse feed	≤ DC 25 V
Oversoltage category	II
Pollution degree	2
Transient suppression (primary)	Varistor
Oversoltage protection; secondary	≤ 30 VDC (in the event of a fault)
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	> 500,000 h (per IEC 61709)

Connection data

Connection type 1	Input/output
Connection technology	CAGE CLAMP®
WAGO connector	WAGO 740 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Strip length	6 ... 7 mm / 0.24 ... 0.28 inches

Physical data

Width	72 mm / 2.835 inches
Height	89 mm / 3.504 inches
Depth	59 mm / 2.323 inches
Depth from upper-edge of DIN-rail	55 mm / 2.165 inches

Mechanical data

Mounting type	DIN-35 rail
---------------	-------------

Material data

Flammability class per UL94	V0
Fire load	0 MJ
Weight	255 g

Environmental requirements

Ambient temperature (operation)	-25 ... +60 °C (Device starts at -40 °C (type-tested))
Ambient temperature (storage)	-25 ... +80 °C
Ambient temperature UL (operation at U _N)	-25 ... +55 °C
Relative humidity	5 ... 96 % (no condensation permissible)
Derating	-3 %/K (> 45 °C)

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61010-1 EN 61010-2-201 EN 61204-3 UL 60950-1 UL 508 DNV

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821297604
Customs tariff number	85044083900

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
EAC Brjansker Zertifizierungs- stelle	TP TC 004/2011,TP TC 020/2011	EAC RU C-DE.AM02. B.00089_19
UL Underwriters Laboratories Inc.	UL 60950-1	E255815

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 787-1011



Documentation

Bid Text			
787-1011	24.06.2019	xml 6.95 KB	
787-1011	12.06.2019	docx 20.76 KB	

Instruction Leaflet			
Power Supply COM-PACT	29-03-2021 20.12.2021	pdf 2143.15 KB	

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 787-1011	EPLAN Data Portal 787-1011
	WSCAD Universe 787-1011
	ZUKEN Portal 787-1011

1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking strip



Item No.: 210-831

Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white

Item No.: 210-832

Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white

1.1.2 Tool

1.1.2.1 Operating tool



Item No.: 210-720

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Item No.: 210-769

SCREWDRIVER; green