

### MATE-N-LOK | Universal MATE-N-LOK

TE Internal #: 350793-3

Rectangular Power Connectors, Header, Receptacle, Wire-to-

Board, 4 Position, 6.35 mm [.25 in] Centerline, Printed Circuit Board,

Universal MATE-N-LOK

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Header

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 4

Centerline (Pitch): 6.35 mm [ .25 in ]

### **Features**

### **Product Type Features**

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	4
PCB Mount Orientation	Vertical
Number of Power Positions	4
Number of Rows	1
Electrical Characteristics	
Operating Voltage	600 VAC
Contact Features	

Without

Multiple Contact Types



PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Contact Layout	Inline
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	10 A, 12 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 – .91 μm[30 – 36 μin]
ermination Features	
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
lechanical Attachment	
Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount
ousing Features	
Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	White
Housing Material	Nylon
Pimensions	
	.03 – .09 in
PCB Thickness (Recommended)	1.57 mm[.062 in]
sage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
peration/Application	



Circuit Application	Power
Industry Standards	
UL Rating	Recognized
Agency/Standard	UL, VDE
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	100
Packaging Method	Bag

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts







































Also in the Series | Universal MATE-N-LOK





Circular Power Connectors(2)



Connector Contacts(7)



Insertion & Extraction Tools(4)



Power Contacts(201)



Rectangular Boots & Strain Relief(34)



Rectangular Connector Adapters(7)



Rectangular Connector Hardware(1)



Rectangular Connector Housings(1)



Rectangular Connector Keying Plugs(3)



Rectangular Connector Seals(26)



Rectangular Power Connectors(662)

# Customers Also Bought



TE Part #1462039-2 IM07CGR=IM RELAY 200mW 24V HDV



TE Part #205163-1
RECEPT ASSY,15 POSN,AMPLIMITE



TE Part #87220-2 02 MODII HDR SRST UNSHRD .100



TE Part #103735-4
05 MTE HDR SRST LATCH .100CL



TE Part #103735-7
08 MTE HDR SRST LATCH .100CL



TE Part #5-1437622-7
KN5700B1/4=KNOB BLACK PAIR 1/8



TE Part #120957-1 UPM EXPANDED PIN ASSEMBLY



TE Part #120953-4
UPM EXPANDED RCPT ASSEMBLY





TE Part #2575010001 TMS-SCE-1/8-2.0-S2-9

### **Documents**

### **Product Drawings**

04P UMNL PIN HDR ASSY 94VO LF

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_350793-3\_W.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_350793-3\_W.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_350793-3\_W.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_350793-3\_R.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_350793-3\_R.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_350793-3\_R.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_SOCKET\_CONNECTORS\_STANDARD\_DENSITY

English

### **Product Specifications**

**Application Specification** 

English



Product Environmental Compliance

TE Material Declaration

English