# **Fume Extraction**

## **BVX-208 Systems**

#### BTX-208

## **Portable Tip Extraction Unit**

Part Number	Description
BTX-208	Filter Unit for 8 Tip Extraction Station with Pre-, HEPA/Gas-Filter
Filters	
FP-BVX200	Pre-Filters (pack of 5)
FM-BVX200	Main Filter, HEPA/Gas (Carbon)





### **System Specification**

BTX-200 Portable Tip Extract	tion Unit
Input Line Voltage	100 - 240 VAC, 50 - 60 Hz
Rated Power	85 W
Air Inlets/Number of solder stations	8
Duct run	30 m (100") max.
Flow Rate per extraction tube	> 28 I/min
HEPA Efficiency	99.97 % at 0.3 micron
Noise Level	< 55 dBA
Dimensions (W x D x H)	508 x 254 x 388 mm (20" x 10" x 15.3")
Weight	9 kg (20 lb)
Certification/Marking	UL, CSA, CE

## **Key Features & Benefits**

#### **High performance extraction**

directly from the tip of any iron

#### Easy extraction network

configuration for up to 8 benches

#### Complete portability

Designed for under-bench installation

### Main filter has a HEPA efficiency of 99.97 %

at 0.3 micron, and an activated carbon filter to remove gases

#### **Both pre- and main- filters**

can be changed independently

### Plug-and-play ducting system

for simple, flexible low cost solution and fast installations

#### Universal hose connection kit



Connection	Kits	
BTX-CK2-25		Connection Kit for 2-4 stations with 2.5 m (8') long hose, Ø 35 mm
BTX-CK4-50		Connection Kit for 4 -8 stations with 5 m (16') long hose, Ø 35 mm
BTX-CK4-75		Connection Kit for 4-8 stations with 7.5 m (25') long hose, Ø 35 mm
Individual Parts		
CH0121	1	Flexible Hose, Ø 35 mm x length 2.5 m (8')
CH0121 CH0122	1	Flexible Hose, Ø 35 mm x length 2.5 m (8')  Flexible Hose, Ø 35 mm x length 5 m 16')
0110121	•	
CH0122	1	Flexible Hose, Ø 35 mm x length 5 m 16')
CH0122 CH0123	1	Flexible Hose, Ø 35 mm x length 5 m 16') Flexible Hose, Ø 35 mm x length 7.5 m (25') Couplings with 2 Glands, Ø 5.6 mm
CH0122 CH0123 AC-TX001-4	1 1 2 3	Flexible Hose, Ø 35 mm x length 5 m 16') Flexible Hose, Ø 35 mm x length 7.5 m (25') Couplings with 2 Glands, Ø 5.6 mm (pack of 4) T-piece Connector, Ø 35 mm (pack of 2)

