

Spring Loaded Connector

multicomp PRO

**RoHS
Compliant**



Specifications

Electrical

Current Rate : 1A
Contact Resistance : 50mΩ

Environmental

Operating Temperature Range : -40°C to +85°C


Mechanical

Spring Force : 30 ±20% gf
Working Stroke : 1.2mm
Durability : 10,000 cycles

Material

Plunger : Brass C3604, 3μ" gold Plating
Barrel : Brass C3604, 3μ" gold Plating
Spring : SUS304
Housing : LCP, Black
Magnet : NdFeB, N52

Diagram



RECOMMEND PCB LAYOUT
Layout Tolerance: ± 0.05mm

General Tolerance

X. = ±0.3mm
.X = ±0.15mm
.XX = ±0.1mm

Part Number Table

Description	Part Number
Spring Loaded Connector, 2 Pin, 2.84mm Pitch, Male	MP011974

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp PRO