

# Programmable Linear Bench Top DC Power Supplies

**multicomp** PRO

**RoHS  
Compliant**



## Description

This series DC power supply with three independent outputs is a cost-effective programmable DC power supply with excellent performance, reliable output and clear interface.

The instrument has constant voltage (CV) and constant current (CC) modes, short-circuit and over-voltage protection functions, which can perfectly meet various test requirements.

## Features

- Maximum power up to 373W
- Four channel independent output: CH1/CH2: 0~30V/5A, CH3: 0~6V/3A, CH4: 5V/ 2A
- Multiple protection: OCP/OVP/OTP
- Excellent load regulation and line regulation
- Ultra low output ripple and noise
- Support one key serial and parallel output function
- The 4.3-inch TFT display can display three channels and multiple parameters at the same time
- List / delayer function to control voltage and current output as required
- External trigger function to realize industrial automation control
- Provide USB host, USB device, LAN, RS232, digital I/O and other interfaces
- With waveform display function, real-time and dynamic display of output voltage / current / power waveform
- Intelligent speed control of fan can effectively reduce fan noise during operation
- Support 10 groups of file storage and transfer out, and support USB flash disk reading and writing
- High precision display of five-digit voltage / four-digit current, with resolutions of 10mV / 1mA and 1mV / 1mA
- Keyboard lock function to prevent misoperation
- Support SCPI remote command control

## Specifications

Model		MP711001
Channel	Channel	4
Output Rating	Voltage	CH1&CH2: 0-32V
		CH3: 0~6V
		CH4: 5V (USB Output )
	Current	CH1&CH2: 0~5A
CH3: 0~3A		
CH4: 2A (USB Output)		
	Power	348W
CV mode	Regulation	Line Regulation: <0.01%+2mV
		Load Regulation: <0.01%+2mV
	Regulation	<350μVrms/ 2mVpp(5Hz~1MHz)
	Reaction time	≤50μs (50% load variation, minimum load 0.5A)
	Command processing time	<100ms

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
sg.element14.com/b/multicomp-pro

**multicomp** PRO

# Programmable Linear Bench Top DC Power Supplies

**multicomp** PRO

Model		MP711001
CC mode	Regulation	Line Regulation: $\leq 0.01\% + 250\mu\text{A}$ Line Regulation: $\leq 0.01\% + 250\mu\text{A}$
	Ripple current	$\leq 2\text{mArms}$
Tracking mode	parallel connection	Line Regulation: $\leq 0.01\% + 2\text{mV}$ Load Regulation: $\leq 0.01\% + 2\text{mV}$
		Line Regulation: $\leq 0.01\% + 3\text{mV}$ Load Regulation: $< 300\text{mV}$
	Tracking error	$\leq 0.5\% + 10\text{mV}$ (10-30V No load) $\leq 0.5\% + 30\text{mV}$ (0-9.99V No load) Access load $< 300\text{mA}$
measure	Display	Voltage full scale, A-digit display: 4.3inchLCD Current full scale, A-digit display: 4.3 inchLCD
		Voltage: 10mV Current: 1mA
	Readback resolution	Voltage: 10mV Current: 1mA
		Voltage: $\pm (0.3\% + 20\text{mV})$ Current: $\pm (0.2\% + 5\text{mA})$
	Readback accuracy (25 $\pm$ 5°C)	Voltage: $\pm (0.1\% + 20\text{mV})$ Current: $\pm (0.15\% + 5\text{mA})$
Voltage programmed speed (1% of the total variation range)	CH1	Rise: full load $< 50\text{ms}$ ; No load $< 30\text{ms}$ Fall: full load $< 45\text{ms}$ ; No load $< 400\text{ms}$
		Rise: full load $< 50\text{ms}$ ; No load $< 30\text{ms}$ Fall: full load $< 45\text{ms}$ ; No load $< 400\text{ms}$
	CH2	Rise: full load $< 15\text{ms}$ ; No load $< 13\text{ms}$ Fall: full load $< 22\text{ms}$ ; No load $< 100\text{ms}$
	CH3	
Temperature coefficient perC° (output percentage + offset)	CH1	Voltage: 0.01%+5mV Current: 0.01%+2mA
		Voltage: 0.01%+5mV Current: 0.01%+2mA
	CH2	Voltage: 0.01%+2mV Current: 0.01%+2mA
	CH3	
Channel 4 (USBoutput)	Output voltage	5V $\pm 0.25\text{V}$
	Output current	2A
Input	Voltage	AC100V/120V/220V/230V $\pm 10\%$
	Frequency	50/60Hz
	Power	MAX 600W
	Fuse	AC220V : T4AL250V ACT10V : T8AL250V

# Programmable Linear Bench Top DC Power Supplies

**multicomp** PRO

<b>Model</b>	<b>MP711001</b>	
Environment	Operating temperature	0°C to 40°C
	Operating humidity	20%~80% (non-condensing)
	Storage temperature	-10°C to 60°C
	Altitude	≤2000m
	Pollution degree	2
Size and weight	Size	355mm × 240mm × 168mm
	Weight	10.2kg

## Part Number Table

Description	Part Number
Programmable Linear Bench Top DC Power Supplies, 4 CH, EU/UK	MP711001

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
sg.element14.com/b/multicomp-pro

**multicomp** PRO