

10-in-1 Cellular, Wi-Fi, GPS Combination IoT Antenna FAKRA Jack ABS Radome Black IP69K

## LCANOM1098



#### **Features**

- 4 x Cellular 4G/5G
- 5 x Wi-Fi 2.4 GHz / 5 GHz
- 1 x GPS L1 / G1
- MIMO Capable

## **Applications**

- · Public Safety
- Emergency Services
- · Mobile Base Stations
- · Autonomous Vehicles

- · Color coded FAKRA Jack
- 17 ft Cable Leads
- Indoor/Outdoor IP69K Rated
- · UV Stabilized Black ABS
- · Fleet Management
- Smart Cities
- · Smart Utilities
- Industrial IoT

## **Description**

The L-Com LCANOM1098 is a 10-in-1 combination antenna designed for public safety, emergency services, mobile base stations, autonomous vehicles, fleet management, smart cities, smart utilities, or industrial IoT applications. This vertically polarized omnidirectional antenna has color-coded FAKRA female connectors with 17 feet cable leads. Our high-quality mobile antenna with 10 ports has a typical input VSWR of 2:1.

The IoT combination antenna from L-Com has an overall length of 7 inches, width of 7 inches, and weight of 4 lbs. This LCANOM1098 mobile antenna is IP69K-rated and has a black-colored radome made of UV-stabilized ABS. The 4 cellular, 5 Wi-Fi, 1 GPS combination antenna has an impedance of 50 Ohms and a maximum input power of 10 Watts.

Our vertically polarized mobile antenna can operate at temperatures ranging from -40 to 70 degrees C. This MIMO-capable IoT antenna features four 4G/5G, five 2.4/5 GHz, and one L1/G1 GPS band elements in one radome. Emergency services, first responders, and fleets can rely on our 10-in-1 combination antenna to maintain a secure link between vehicles and dispatch centers.

### Configuration

Design Radiation Pattern Polarization Connector Type Number of Ports Mobile Omni Directional Vertical FAKRA Female 10

### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Input VSWR		2:1		
Impedance		50		Ohms
Input Power			10	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 10-in-1 Cellular, Wi-Fi, GPS Combination IoT Antenna FAKRA Jack ABS Radome Black IP69K LCANOM1098



10-in-1 Cellular, Wi-Fi, GPS Combination IoT Antenna FAKRA Jack ABS Radome Black IP69K

# LCANOM1098



Cellular Specifications					
Frequency Range	617 - 960	1690 - 2700	3300 - 4200	4900 - 6000	MHz
Peak Gain	4	6	7	8	dBi
Port Count		4	1		
Cable Type		RG	58		
Cable Length		17	[5]		ft [m
Connector Type		FAKRA	A Jack		
Connector Color		Bord	eaux		
Connector Code		0	)		
Wi-Fi Specifications					
Frequency Range	2400	- 2500	4900 -	6000	MHz
Peak Gain		5	6	i	dBi
Port Count		5	5		
Cable Type		RG	58		
Cable Length		17	[5]		ft [m
Connector Type		FAKRA	A Jack		
Connector Color		Bei	ige		
Connector Code		I			
GPS Specifications					
Frequency Range		1562 -	1612		MHz
VSWR		<2.0:1 ±	4 MHz		
LNA Gain		2	6		dB
Out of band rejection		>40 dB (@ > -	+/- 100 MHz)		
Typical Noise Figure		≤ 2	2.7		dB
Notch Filter rejection @787MHz		24	4		dB
Operating Voltage		3 -	. 5		VDC
Typical Current		1	5		mA
Cable Type / Length		RG174 / 1	7 ft [5 m]		
Connector Type		FAKRA	A Jack		
Connector Color / Code		Blue	e / C		



10-in-1 Cellular, Wi-Fi, GPS Combination IoT Antenna FAKRA Jack ABS Radome Black IP69K

## LCANOM1098



## **Mechanical Specifications**

Radome Material UV Stabilized ABS

Size

 Length
 7 in [177.8 mm]

 Width
 7 in [177.8 mm]

 Height
 3.15 in [80.01 mm]

 Weight
 4 lbs [1.81 kg]

**Environmental Specifications** 

**Temperature** 

Operating Range -40 to +70 deg C

Ingress Protection IP69

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

10-in-1 Cellular, Wi-Fi, GPS Combination IoT Antenna FAKRA Jack ABS Radome Black IP69K from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

## **L-com CAD Drawing**

