



PSKN Series in Straight Position

PSN in fixed straight position

PSNRA in fixed right angle position

## Device Antennas, Halfwave, LTE 3G/4G Dual-band, 694-2750 MHz

- Sleek profile with adjustable elbow for straight or angled operation
- Compact design, ground plane independent with high performance
- Can be configured as fixed straight or fixed right angle (prefix PSN or PSNRA)

The PSKN Dual band antennas offer excellent performance and are available for a number of dualband and broadband wireless data applications.

Three different series are available; a model for US Cellular 3G, a model for EU GSM, and a wideband model for US Cellular including GSM/CDMA, LTE & AWS/UMTS.

The EU GSM 925 MHz lower band also covers with the ISM 915 band (902-928 MHz), without any sacrifice in performance. Additionally, a model is available with reverse polarity SMA connector, for use in ISM 915.

The broadband options, PSKN3-700/2100S and PSKN3-700/2700S, cover traditional cellular frequencies as well as the new LTE 700 MHz band and the UMTS bands.

This PSKN series is a “blade” style antenna with an adjustable right angle elbow. Overall length is 7.75” (20 cm) in a straight position, and 6.75” (17.2 cm) in a right angle position. Peak gain on all bands is 3 dBi.

The halfwave design means the antennas are ground-plane independent; the antennas can be used on plastic or metal without concern for proper ground size.

The radome material is a semi-flex polyurethane, providing some give when stressed but maintaining long term durability.

The antennas pass a number of industrial and military shock & vibration standards, and have been rated IPx5 for water ingress. The PSN models are rated IP67.

The antennas are available with SMA, TNC or Reverse Polarity SMA (for 902-928 ISM applications).

Model #	Frequency (MHz)	Connector
<b>US CDMA/GSM/Data</b>		
PSKN3-900/1900T	824-894 & 1850-1990	TNC Plug
PSKN3-900/1900S	824-894 & 1850-1990	SMA Plug
<b>EU GSM &amp; ISM 915</b>		
PSKN3-925/1800S	870-960 & 1710-1880	SMA Plug
PSKN3-925/1800T	870-960 & 1710-1880	TNC Plug
<b>EU GSM &amp; ISM 915 with Rev Pol SMA</b>		
PSKN3-925/1800RS	870-960 & 1710-1880	Rev SMA Plug
<b>Wideband with SMA</b>		
PSKN3-700/2100S	694-960 & 1710-2170	MA Plug
PSKN3-700/2700S	694-960 & 1710-2750	SMA Plug

All Knuckle-Swivel Models (PSKN) Available in Fixed Position:  
 PSN - Straight Fixed Position. PSNRA - Right Angle Fixed Position.

### Specifications

Frequency ranges:	824-894 & 1850-1990 MHz
900/1900	870-960 & 1710-1880 MHz
925/1800	694-960 & 1710-2170 MHz
700/2100	694-960 & 1710-2750 MHz
700/2700	3 dBi peak
Gain:	2:1 max over range
VSWR:	50 Ohm nominal
Impedance:	5 Watt
Maximum Power:	-40°C to +85°C
Operating Temp:	SMA Plug (Male), TNC Plug (Male), or Reverse Pol SMA
Connector:	

Whip Length:	6.75” (17.2 cm) at 90° angle, 7.75” (19.7 cm) when straight
Radome Material:	Polyurethane, with black matt finish, and knurled connector.
Shock & Vibration:	EN 61373, IEEE 1478, MIL-810G, TIA-329.2-C
Water Ingress:	IP67 (PSN series) IPx5 (others)
Style:	
PSKN	Adjustable Straight, Right Angle
PSN	Fixed Straight
PSNRA	Fixed Right Angle