

SPECIFICATION FOR APPROVAL

承 認 書

Description : Piezo Audio Transducer
Kingstate Part No. : KPEG131H-40L
Customer's Model No. : _____
Specification No. : POD-5639
Number Of The Edition : 1.1

CUSTOMER'S APPROVED SIGNATURE		



KINGSTATE


志豐電子股份有限公司 KINGSTATE ELECTRONICS CORP.

Address : 10F, No. 69-11, Sec. 2, Chung Cheng E. Rd., Tamshui County, Taipei Hsien, Taiwan, R.O.C.

International sales dept.: TEL:886-2-2809-5651 FAX:886-2-2809-7151

Domestic sales dept.: TEL:886-2-2809-0668 FAX:886-2-28096748

<http://www.kingstate.com.tw>

Approved by	Checked by	Issued by
 2019.11.21	陈中煌 2019/11/21	HUANGJIE 2019/11/21

A.SCOPE 範疇


This specification applies piezo audio transducer, **KPEG131H-40L**

此規格書適用於壓電式蜂鳴器, **KPEG131H-40L**

B. SPECIFICATION 規格

No.	Item	Unit	Specification	Condition
1	Operating Frequency 操作頻率	Hz	3.2±0.5	只代表電路輸出頻率
2	Operating Volt.range 操作電壓範圍	VDC	6~15	
3	Current consumption 消耗電流	mA	Max 70	Driven by RE46C100 14VDC
4	Sound pressure level 輸出音壓	dB	Min 100	at 30cm Driven by RE46C100 14VDC
			Min 80	at 300cm/30Vp-p,square wave,3.15KHz
5	Tone 聲音		Continuous 直音	
6	Operating temp. 操作溫度	°C	-40 ~ +80	
7	Storage temp. 儲存溫度	°C	-40 ~ +85	
8	Dimension 尺寸	mm	φ 39 x H7.6	See appearance drawing 請參照外觀尺寸圖
9	Weight (MAX) 重量	gram	8.5	
10	Material 材質		PBT UL 94 V-0 (BLACK)	
11	Terminal 端子		Wire type	
12	Environmental Protection Regulation 環保法規		RoHS 2.0	Piezo electronic device is exempted from RoHS2.0. Lead contain restriction. 電子陶瓷產品不受 RoHS2.0 條款規範

C. APPEARANCE DRAWING 外觀尺寸圖



WIRE : UL1571 AWG30#

Connector Housing : CHYAO YEE JVT1146HN0-03N /Pitch 1.25mm


Connector : CHYAO YEE JVT1146TP-SNS

Tol: ± 0.5

Unit: mm

D. MEASURING METHOD 測量方法


1. S.P.L. Measuring Circuit 音壓測試接線圖



Mic : RION S.P.L. meter UC30 or equivalent


Mic : RION 噪音計 UC30 或同等品

2. The current consumption and the sound pressure level are measured by using the recommend driving circuit shown as below (one example) 當前的測試數據是依靠此電器迴路所量測



Note 1: Place C2 close to the device power pins to minimize horn switching noise.


E. VOLTAGE: SOUND PRESSURE LEVEL / VOLTAGE: CURRENT CONSUMPTION CHARACTERISTICS 電壓與音壓/電壓與耗電流之特性



F. MECHANICAL CHARACTERISTICS 機械特性

No.	Item	Test Condition	Evaluation standard
1	Solderability 焊錫附着性 (Connector excepted) (端子線類不適用)	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of +270±5°C for 3±1 seconds. 端子部份浸入松香溶液 5 秒後,再浸入+270±5°C 熔融焊錫槽中 3±1 秒.	90% min. lead terminals shall be wet with solder. (Except the edge of terminal) 浸入端子部份附着焊錫 90% 以上.(末端斷面不算)
2	Soldering Heat Resistance 焊錫耐熱性 (Connector excepted) (端子線類不適用)	Lead terminal are immersed up to 1.5mm from sounder's body in solder bath of +300±5°C for 3±0.5 seconds or +260±5°C for 10±1 seconds. 距離端子根部 1.5mm 的位置,浸入+300±5°C 的焊錫槽 3±0.5 秒,或+260±5°C 的焊錫槽 10±1 秒.	No interference in operation 操作上無任何不良.
3	Terminal Mechanical Strength 端子強度 (Connector excepted) (端子線類不適用)	The force 10 seconds of 9.8N (1.0kg) is applied to each terminal in axial direction. 各端子的軸方向施以 9.8N (1.0kg) 的力量 10 秒.	No damage and cutting off 端子不鬆動, 不脫落.
4	Vibration 振動試驗	Buzzer shall be measured after being applied vibration of amplitude of 1.5mm with 10 to 55hz band of vibration frequency to each of 3 per-pendicular directions for 2 hours. 振動週波數 10~55HZ、全振幅 1.5mm 於 X.Y.Z 3 個方向,各 2 小時.	The value of oscillation frequency/ current consumption should be in 10% compared with initial ones. The SPL should be in ±10dB compared with initial one.
5	Drop test 落下測試	The part only shall be dropped from a height of 75cm onto a 40mm thick wooden board 3 times in 3 axes (X.Y.Z). (a total of 9 times). 單體從 75 公分高處, X.Y.Z.3 個方向,各 3 回,落於 40mm 厚木板上.	諧振頻率與消耗電流變化量須在 ±10% 內. 輸出音壓變化量須在 ±10dB 內.

G. ENVIRONMENT TEST 環境測試

No.	Item	Test Condition	Evaluation standard
1	High temp. test 高溫測試	After being placed in a chamber at +85°C for 240 hours 置於+85°C環境中 240 小時	Being placed for 4 hours at +25°C, buzzer shall be measured. The value of oscillation frequency/ current consumption should be in±10% compared with initial ones .The SPL should be in±10dB compared with initial one. 經測試後，靜置於+25°C（室溫）環境中 4 小時後，諧振頻率與消耗電流變化量須在±10%內。輸出音壓變化量須在±10dB 內。
2	Low temp. test 低溫測試	After being placed in a chamber at -30°C for 240 hours 置於-30°C環境中 240 小時	
3	Humidity test 相對濕度測試	After being placed in a chamber at +40°C and 90±5% relative humidity for 240 hours 置於+40°C，相對濕度 90±5% 環境中 240 小時	
4	Temp. cycle test 溫度循環試驗	The part shall be subjected to 5 cycles. One cycle shall consist of: 單體承受溫度循環測試 5 次，其循環內容如圖示： 	


H. RELIABILITY TEST 信賴性測試



No.	Item	Test condition	Evaluation standard
1	Operating lifetest 壽命測試	<p>1. Continuous life test 高溫壽命測試(連續) 48 hours continuous operation at +65°C with rated voltage applied. 在+65°C環境下，以額定電壓連續操作 48 小時</p> <p>2. Intermittent life test 室溫壽命測試(間歇) A duty cycle of 1 minute on, 1 minutes off, a minimum of 5000 times at room temp.(+25±2°C) and rated voltage applied 在室溫下(+25±2°C)，以額定電壓操作，通電 1 分鐘/斷電 1 分鐘，測試 5000 次循環。</p>	Being placed for 4 hours at +25°C, buzzer shall be measured. The value of oscillation frequency/ current consumption should be in ±10% compared with initial ones .The SPL should be in ±10dB compared with initial one. 經測試後，靜置於+25°C（室溫）環境中 4 小時後，諧振頻率與消耗電流變化量須在±10%內。輸出音壓變化量須在±10dB 內。

TEST CONDITION.



Standard Test Condition 一般測試條件	:	a) Temperature: +5 ~ +35°C b) Humidity: 45-85% c) Pressure: 860-1060mbar
Judgement Test Condition 爭議時測試條件	:	a) 溫度: +5 ~ +35°C b) 濕度: 45-85% c) 氣壓: 860-1060mbar
	:	a) Temperature: +25 ± 2°C b) Humidity: 60-70% c) Pressure: 860-1060mbar
	:	a) 溫度: +25 ± 2°C b) 濕度: 60-70% c) 氣壓: 860-1060mbar

I. PACKING STANDARD 包裝規格



Lot No.	XXXXXXXXXX
Part No.	XXXXXXXXXX
Quantity	XXXX PCS
Date:	DD MM YY
	
	

* The label sticked on inner boxes and the outer of carton.



Out Box	310mmx250mmx14mm	20PCS
Carton Box	550mmx330mmx290mm	20x40=800PCS