



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 1.8-20W G4 827

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers significant energy savings and minimises maintenance costs without any compromise on light quality.

Product data

General information	
Lighting Technology	LED
Flux measurement reference	Sphere
Switching Cycle	50,000
Nominal lifetime	15,000 h
Cap base	G4 [G4]
Light technical	
Colour Code	827 [CCT of 2700K]
Beam angle (nom.)	300 degree(s)
Luminous Flux	205 lm
Colour designation	Warm White (WW)
Correlated Colour Temperature	2700 K
Luminous Efficacy (rated) (Nom)	113.00 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %
Flickering value (PstLM)	0.4

Stroboscopic effect	1
Operating and electrical	
Line Frequency	- Hz
Input frequency	- Hz
Power Consumption	1.8 W
Lamp current (nom.)	260 mA
Wattage equivalent	20 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (nom.)	ac electronic 12 V
Temperature	
T-Case maximum (nom.)	80 °C
Controls and dimming	
Dimmable	No


Datasheet, 2023, May 22 data subject to change

CorePro LEDcapsule LV

Mechanical and housing	
Bulb shape	Capsule
Approval and application	
Energy Efficiency Class	F
Suitable for accent lighting	No
Energy consumption kWh/1,000 hours	2 kWh
EPREL registration number	374873
CE mark	Yes
EU RoHS compliant	Yes


Product data	
Full EOC	871869976765500
Order product name	CorePro LEDcapsuleLV 1.8-20W G4 827
Order code	76765500
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
Material number (12NC)	929002389002
Full product name	CorePro LEDcapsuleLV 1.8-20W G4 827
EAN/UPC - Case	8718699767662


Dimensional drawing



Product	D	С
CorePro LEDcapsuleLV 1.8-20W G4 827	13 mm	35 mm

Photometric data






Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.8-20W G4 827

Light Distribution Diagram - CorePro LEDcapsuleLV 1.8-20W G4 827

CorePro LEDcapsule LV


Photometric data




Calculut Photometrics 4.5 Philips Lighting SLV. Pages 19

General uniform lighting - CorePro LEDcapsuleLV 1.8-20W G4 827

Lifetime





Life Expectancy Diagram - CorePro LEDcapsuleLV 1.8-20W G4 827

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 1.8-20W G4 827



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.