

# DATA SHEET

## TRANSIENT VOLTAGE SUPPRESSORS

### AC/DC POWER SUPPLY

1.0SMB-AT series

RoHS compliant & Halogen free



Product specification— June 30, 2023 V.1



## Transient Voltage Suppressors (TVS) Data Sheet

### Features

- For surface mounted applications in order to optimize board space
- Low profile package
- Built-in strain relief
- Glass passivated junction
- Low inductance
- Excellent clamping capability
- 1000W peak pulse power capability at 10/1000 $\mu$ s waveform, repetition rate (duty cycle): 0.01%
- Fast response time
- Typical  $I_R$  less than 1 $\mu$ A above 12V
- High Temperature soldering: 260 $^{\circ}$ C/10 seconds at terminals
- Plastic package has underwriters laboratory flammability 94V-0
- Meets MSL level 1, per J-STD-020
- AEC-Q101 qualified
- IEC61000-4-2 ESD 30KV Air, 30KV contact compliance



### Mechanical Data

- Case: JEDEC DO-214AA. Molded plastic over glass passivated junction
- Terminal: Tin plated, solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode except bi-directional models
- Standard Packaging: 12mm tape (EIA STD RS-481)
- Weight: 0.10g

### Applications

- I/O interface
- AC/DC power supply
- Low frequency signal transmission line (RS232, RS485, etc.)

**Maximum Ratings and Characteristics**

Ratings at 25°C ambient temperature unless otherwise specified.

Rating	Symbol	Value	Units
Peak pulse power dissipation at 10/1000µs waveform (Note1, Note2, Fig.1)	$P_{PPM}$	Minimum 1000	Watts
Peak pulse current of at 10/1000µs waveform (Note 1, Fig.3)	$I_{PPM}$	See Table	Amps
Steady state power dissipation at $T_A=50^\circ\text{C}$ (Fig.5)	$P_{M(AV)}$	5.0	Watts
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load, (JEDEC Method) (Note3, Fig.6)	$I_{FSM}$	100	Amps
Operating junction and Storage Temperature Range.	$T_J, T_{STG}$	-55 to +150	°C
Typical thermal resistance junction to lead	$R_{\theta JL}$	20	°C/W
Typical thermal resistance junction to ambient	$R_{\theta JA}$	100	°C/W

Notes: 1. Non-repetitive current pulse, per Fig.3 and derated above  $T_A=25^\circ\text{C}$  per Fig.2.

2. Mounted on 5.0mmx5.0mm (0.03mm thick) copper pads to each terminal.

3. 8.3ms single half sine-wave, or equivalent square wave, duty cycle=4 pulses per minutes maximum.

**Dimensions (SMB/DO-214AA)**

Product:	Symbol	Millimeters		Inches	
		Min.	Max.	Min.	Max.
<p>Product:</p> <p>Cathode Band</p> <p>Pad:</p>	L	4.06	4.57	0.160	0.180
	D	3.30	3.94	0.130	0.155
	D1	1.95	2.20	0.077	0.086
	T	5.21	5.59	0.205	0.220
	T1	0.76	1.52	0.030	0.060
	d	-	0.203	-	0.008
	H	2.15	2.65	0.085	0.104
	H1	2.13	2.47	0.084	0.097

## Transient Voltage Suppressors

1.0SMB-AT

Electrical Characteristics (T<sub>A</sub>=25°C)

Part Number		Device Marking Code		Reverse Stand-Off Voltage	Breakdown Voltage @I <sub>T</sub>	Test Current	Maximum Clamping Voltage @I <sub>PP</sub>	Peak Pulse Current	Reverse Leakage @V <sub>RWM</sub>
Unidirectional	Bidirectional	UNI	BI	V <sub>RWM</sub> (V)	V <sub>BR</sub> (V)	I <sub>T</sub> (mA)	V <sub>C</sub> (V)	I <sub>PP</sub> (A)	I <sub>R</sub> (μA)
1.0SMB6.8A-AT	1.0SMB6.8CA-AT	6K8A	6K8C	5.80	6.45~7.14	10	10.5	96.8	1000
1.0SMB7.5A-AT	1.0SMB7.5CA-AT	7K5A	7K5C	6.40	7.13~7.88	10	11.3	90.0	500
1.0SMB8.2A-AT	1.0SMB8.2CA-AT	8K2A	8K2C	7.02	7.79~8.61	10	12.1	84.0	200
1.0SMB9.1A-AT	1.0SMB9.1CA-AT	9K1A	9K1C	7.78	8.65~9.55	1	13.4	75.8	50
1.0SMB10A-AT	1.0SMB10CA-AT	K10A	K10C	8.55	9.50~10.50	1	14.5	70.2	10
1.0SMB11A-AT	1.0SMB11CA-AT	K11A	K11C	9.40	10.50~11.60	1	15.6	65.2	5
1.0SMB12A-AT	1.0SMB12CA-AT	K12A	K12C	10.20	11.40~12.60	1	16.7	60.8	5
1.0SMB13A-AT	1.0SMB13CA-AT	K13A	K13C	11.10	12.40~13.70	1	18.2	55.8	1
1.0SMB15A-AT	1.0SMB15CA-AT	K15A	K15C	12.80	14.30~15.80	1	21.2	48.0	1
1.0SMB16A-AT	1.0SMB16CA-AT	K16A	K16C	13.60	15.20~16.80	1	22.5	45.2	1
1.0SMB18A-AT	1.0SMB18CA-AT	K18A	K18C	15.30	17.10~18.90	1	25.5	40.3	1
1.0SMB20A-AT	1.0SMB20CA-AT	K20A	K20C	17.10	19.00~21.00	1	27.7	36.7	1
1.0SMB22A-AT	1.0SMB22CA-AT	K22A	K22C	18.80	20.90~23.10	1	30.6	33.2	1
1.0SMB24A-AT	1.0SMB24CA-AT	K24A	K24C	20.50	22.80~25.20	1	33.2	30.7	1
1.0SMB27A-AT	1.0SMB27CA-AT	K27A	K27C	23.10	25.70~28.40	1	37.5	27.2	1
1.0SMB30A-AT	1.0SMB30CA-AT	K30A	K30C	25.60	28.50~31.50	1	41.4	24.5	1
1.0SMB33A-AT	1.0SMB33CA-AT	K33A	K33C	28.20	31.40~34.70	1	45.7	22.2	1
1.0SMB36A-AT	1.0SMB36CA-AT	K36A	K36C	30.80	34.20~37.80	1	49.9	20.3	1
1.0SMB39A-AT	1.0SMB39CA-AT	K39A	K39C	33.30	37.10~41.00	1	53.9	18.8	1
1.0SMB43A-AT	1.0SMB43CA-AT	K43A	K43C	36.80	40.90~45.20	1	59.3	17.2	1
1.0SMB47A-AT	1.0SMB47CA-AT	K47A	K47C	40.20	44.70~49.40	1	64.8	15.7	1
1.0SMB51A-AT	1.0SMB51CA-AT	K51A	K51C	43.60	48.50~53.60	1	70.1	14.5	1
1.0SMB56A-AT	1.0SMB56CA-AT	K56A	K56C	47.80	53.20~58.80	1	77.0	13.2	1
1.0SMB62A-AT	1.0SMB62CA-AT	K62A	K62C	53.00	58.90~65.10	1	85.0	12.0	1
1.0SMB68A-AT	1.0SMB68CA-AT	K68A	K68C	58.10	64.60~71.40	1	92.0	11.0	1

**Ratings and Characteristic Curves ( $T_A=25^\circ\text{C}$  unless otherwise noted)**

Figure 1. Peak Pulse Power Rating Curve




Figure 2. Pulse Derating Curve




Figure 3. Pulse Waveform




Figure 4. Typical Junction Capacitance




Figure 5. Steady State Power Dissipation Derating Curve






Figure 6. Maximum Non-Repetitive Forward Surge Current Uni-Directional Only



**Recommended Soldering Conditions**


Reflow Soldering




Recommended Conditions

Profile Feature	Pb-Free Assembly
Average ramp-up rate ( $T_L$ to $T_P$ )	3°C/second max.
Preheat	
-Temperature Min ( $T_{S\ min}$ )	150°C
-Temperature Max ( $T_{S\ max}$ )	200°C
-Time (min to max) ( $t_s$ )	60-180 seconds
$T_{S\ max}$ to $T_L$	
-Ramp-up Rate	3°C/second max.
Time maintained above:	
-Temperature ( $T_L$ )	217°C
-Time ( $t_L$ )	60-150 seconds
Peak Temperature ( $T_P$ )	260°C
Time within 5°C of actual Peak Temperature ( $t_P$ )	20-40 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

**Marking Code**



**Part Number Code**



**Ordering Code for Different Package**

7 inch reel package: Add suffix “/7” at the end of the part number, such as 1.0SMBXXXCA-AT/7

13 inch reel package: Add suffix “/13” at the end of the part number, such as 1.0SMBXXXCA-AT/13

**Packaging**

Tape		Symbol	Dimension (mm)		
		W	12.00±0.20		
		P0	4.00±0.10		
		P1	8.00±0.10		
		P2	2.00±0.10		
		D0	Φ1.55±0.10		
		D1	Φ1.5±0.10		
		E	1.75±0.10		
		F	5.50±0.10		
		A0	3.86±0.15		
		B0	5.65±0.10		
		K0	2.75±0.15		
		T	0.25±0.05		
		7" Reel		D2	Φ178.0±2.0
				D3	Φ50.0Min.
D4	Φ13.0±0.5				
W1	16.0±2.0				
Quantity: 500PCS					
13" Reel				D5	Φ330.0±2.0
		D6	Φ13.5±0.5		
		H	2.5±1.0		
		W2	16.0±2.0		
		Quantity: 3000PCS			

## LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial or automotive grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.