NSYCU1650W230VL

Climasys Cooling Unit 1650W, 3-400V/50Hz-440V/60Hz, lateral mounting, Ral 7035

Main

Range	ClimaSys
Product name	CU
Product or Component Type	Cooling unit
Mounting type	Sides of enclosure
Installation	Indoor side
Mounting Mode	Side
Supply Voltage	230 V AC 50/60 Hz
Rated Power	1650 W
Cooling power	1650 W 50 Hz L35-L35 1700 W 60 Hz L35-L35 1300 W 50 Hz L35-L50 1400 W 60 Hz L35-L50

Complementary

Height	39.37 in (1000 mm)	
Width	15.75 in (400 mm)	
Depth	8.66 in (220 mm)	
Line Rated Current	4.2 A 4.9 A	
Inrush current	18.5 A 16.1 A	
Power consumption in W	800 W 50 Hz, L35-L35 920 W 60 Hz, L35-L35 920 W 50 Hz, L35-L50 1100 W 60 Hz, L35-L50	
Energy efficiency ratio	2.1 1.9	
Control Type	Thermostat	
Temperature setting range	68122 °F (2050 °C)	
Ambient air temperature for operation	Maximum 131 °F (55 °C)	
Noise level	67 dB	
Flow rate	External circuit 163789.61 Gal/hr(US) (620 m3/h) 50 Hz External circuit 179640.21 Gal/hr(US) (680 m3/h) 60 Hz Internal circuit 145297.23 Gal/hr(US) (550 m3/h) 50 Hz Internal circuit 158506.07 Gal/hr(US) (600 m3/h) 60 Hz	
Output Type	Alarm output inverter contact	
Net Weight	92.59 lb(US) (42 kg)	
Cooling gas type	R134a 1.65 lb(US) (0.75 kg))	
Type of filter	External circuit	
Protection type	Thermal protection T 6 A	
Material	Steel	
Color	Gray RAL 7035)	

Environment

IP degree of protection IP34 IEC 60529 on the external circuit) IP54 IEC 60529 on the internal circuit)

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES	
Discount Schedule	ES1	
GTIN	03606480152962	
Returnability	No	
Country of origin	IT	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

|--|