



Polymer Processing



NSF Registered:
category H1, no. 161560



Halal Certified Product:
AN001183

EJECTOR PIN LUBRICANT FG

MOULD TOOL LUBRICANT

Ejector Pin Lubricant FG is a unique blend of highly refined mineral oils, extreme pressure additives and de-watering and anti-corrosion agents. Specifically developed for use on Ejector Pins and Locator Plugs, where a long lasting, high cling release film is required.

PRODUCT CODES / FILL SIZES



31549 / 400ml

APPLICATIONS

The heavy duty lubricating film offers outstanding performance under conditions of extreme pressure and loading on all moving and mechanical parts.

Presented as a completely clear, hard-working film, Ejector Pin Lubricant is non-staining and will not fling off the moving part and is not displaced under high pressure/load operating conditions.

Apply directly onto the part to be treated. The residual film will displace moisture and provide excellent lubrication and protection against corrosion.

DIRECTIONS

- Apply directly onto the part to be treated.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, oily liquid
Odour	Characteristic hydrocarbon
SG @ 20°C	0.83
Temperature Range	-25°C at 250°C
Solubility	Soluble in hydrocarbon solvents, insoluble in water
Recommended Solvents	Ambersil Solvent Cleaner FG, Ambersil Industrial Degreaser FG
Flammability	Classified as extremely flammable under current EC Regulations

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 4.0
Created: July 2019
Updated: June 2021

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

