

#### **Product information**

### 79 02 120 ESD

#### **Precision Electronics Side Cutter ESD**

DIN ISO 9654 DIN EN 61 340-5

General

Head width (A)

**ESD** 



- · Electrically discharging handles dissipative
- Mini-head
- Precision pliers for ultra fine cutting work, e. g. in electronics and fine
- Very precisely ground and sharp cutting edges with very small bevels for exact cutting on delicate electronic components; also available without bevel for flush cutting
- Precision cutting edges additionally induction-hardened, cutting edge hardness approx. 64 HRC
- Approx. 20% lighter than conventional electronics pliers
- Bolted joint with carefully manufactured joint surfaces for even, lowfriction movement throughout the entire opening range
- Smooth-running double spring for a gentle and even opening
- Ergonomically optimised multi-component handles
- Ball bearing chrome steel, forged, multi stage oil-hardened

|      | 19 02 120 12                  |
|------|-------------------------------|
| 40   |                               |
|      |                               |
|      | Cu max. Ø 1,4/hard max. Ø 0,6 |
|      | 2 1,4/hard max. Ø 0,6         |
|      |                               |
| MM 🛦 |                               |

| Article No.                                    | 79 02 120 ESD                |
|--|------------------------------|
| EAN  | 4003773061595                |
| Pliers   | burnished                    |
| Head   | polished                     |
| Handles  | with multi-component grips   |
| Weight   | 57 g                         |
| Dimensions                                     | 120 x 69 x 20 mm             |
| Standard                                       | DIN ISO 9654 DIN EN 61 340-5 |
| REACH compliant                                | does not contain SVHC        |
| RoHS compliant                                 | not applicable               |
| Technical details                              |                              |
| Cutting capacities medium hard wire (diameter) | Ø 1.0 mm                     |
| Cutting capacities hard wire (diameter)        | Ø 0.6 mm                     |
| Cutting capacities soft wire (diameter)        | Ø 0.2 – 1.4 mm               |
| Jaw length (B)                                 | 6.5 mm                       |
| Jaw thickness (joint) (D)                      | 6.5 mm                       |


9 mm

yes

# **KNIPEX** Quality – Made in Germany



## **Technical details**



technical change and errors excepted

