

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

EEPROM 11 Click





PID: MIKROE-5889

EEPROM 11 Click is a compact add-on board with a highly reliable, nonvolatile memory solution. This board features the <u>S-34C04AB</u>, an EEPROM for DIMM serial presence detection from <u>ABLIC</u>. The EEPROM is internally organized as 2 pages of 256 words x 8-bit, and a capacity of 4Kbits and is an EE1004-1 JEDEC standard-compliant. The page write and sequential read are available over the I2C interface. This Click board ™ makes the perfect solution for the development of consumer electronics, office equipment, communication devices, medical equipment, automobile equipment, and more.

EEPROM 11 Click is supported by a $\underline{\mathsf{mikroSDK}}$ compliant library, which includes functions that simplify software development. This $\underline{\mathsf{Click}}\ \mathsf{board}^{\mathsf{TM}}$ comes as a fully tested product, ready to be used on a system equipped with the $\underline{\mathsf{mikroBUS}^{\mathsf{TM}}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Specifications

Туре	EEPROM
Applications	Can be used for the development of consumer electronics, office equipment, communication devices, medical equipment, automobile equipment, and more.
On-board modules	S-34C04AB - EEPROM memory for DIMM serial presence detection from ABLIC
Key Features	EEPROM for DIMM serial presence detect, can write 16 bytes per page, long endurance and data retention, JEDEC standard-compliant, low-current operation, write protection, noise suppression, and more
Interface	I2C
ClickID	Yes
Compatibility	mikroBUS
Click board size	S (28.6 x 25.4 mm)
Input Voltage	3.3V

Resources

<u>mikroBUS™</u>

mikroSDK

Click board™ Catalog

Click Boards™


Downloads

EEPROM 11 click example on Libstock

S-34C04A datasheet

EEPROM 11 click 2D and 3D files

EEPROM 11 click schematic







health and safety management system.