Micro D Connector

multicomp PRO

RoHS Compliant


Specifications

Current Rating
Dielectric Withstanding
Insulation Resistance
Contact Resistance
Operating Temperature
Connector Shell
Pin Contact (Twist Pin)
Socket
Insulator


: 3 Amp


- : 600V AC (Sea level)
- : 5000MΩ Min.
- : 8 million ms (Max.)
- : -55°C to +125°C
- : Aluminium Alloy with electronic Nickel Plating
- : Becu copper with Gold Plating
- : Phos Bronze with Gold plating : PBT

Diagram



29.71





No.	Description	Material	Plating	Qty
1.	Body	Aluminium	Nickel Plate	1
2.	Contact	Bronze	Gold Plate	25
3.	Insulator	PBT	-	1
4.	Socket	Bronze	Gold Plate	25

Part Number Table

Description	Part Number
Micro D Connector, 25 Sockets, Female Side, Right Angle PCB Contact Termination	MP013362

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

