# **Detailed Specifications & Technical Data**



## ENGLISH MEASUREMENT VERSION

# 9717 Multi-Conductor - High-Conductivity Copper Speaker Cable Parallel Zip Const



For more Information please call

1-800-Belden1



# **Description:**

14 AWG stranded (19x27) ETP high-conductivity copper conductors, PVC insulation, parallel: (1) tinned, (1) bare.

## **Physical Characteristics (Overall)**

# Conductor

- A1	۱A/	C.	
_	**	С.	

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
1	14	19x27	High Conductivity TC - Tinned Copper	.071
1	14	19x27	High Conductivity BC - Bare Copper	.071

#### Insulation

## Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC - Polyvinyl Chloride	.035

#### **Outer Shield**

Outer Shield Material:

Outer Shield Material Unshielded

#### **Outer Jacket**

Outer Jacket Material:

Outer Jacket Material

PVC - Polyvinyl Chloride

#### **Overall Cabling**

**Overall Nominal Diameter:** 

0.146 x 0.292 in.

Mechanical Characteristics (Overall)	
Operating Temperature Range:	-20°C To +60°C
Non-UL Temperature Rating:	60°C
Bulk Cable Weight:	36.200 lbs/1000 ft.
Max. Recommended Pulling Tension:	125 lbs.
Min. Bend Radius (Install)/Minor Axis:	3 in.

# Applicable Specifications and Agency Compliance (Overall)

oplicable Standards & Environmental Prog	rams
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes



# 9717 Multi-Conductor - High-Conductivity Copper Speaker Cable Parallel Zip Const

MII Order #39 (China RoHS):	Yes		
Plenum/Non-Plenum			
Plenum (Y/N):	No	 	 
Electrical Characteristics (Overall)			
Nom. Inductance:			
Inductance (µH/ft) .20			
Nom. Conductor DC Resistance:			
DCR @ 20°C (Ohm/1000 ft) 2.70			
Max. Operating Voltage - Non-UL:			
Voltage 300 V RMS			
Max. Recommended Current:			
Current			
9.5 Amps per conductor @ 25°C			

#### **Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9717 368U1000	1,000 FT	42.000 LB	CLEAR, TRANSPARENT		2#14 PVC PARALLEL
9717 3681000	1,000 FT	42.000 LB	CLEAR, TRANSPARENT	С	2#14 PVC PARALLEL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-14-2007

© 2008 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.