




Description

36 Way Centronics Male to Male cable for use with printers and other parallel devices

Specifications

Connector Type A : Centronics Plug, 36 Way
 Connector Type B : IEEE 1284 C36M, Centronics Plug, 36 Way
 Cable Length : 6.6ft (2m)
 Jacket Colour : Grey

Diagram



No	Description	Qty
1	CN36 Male, Gold Flash on contacts, Blue Insulator	2
2	Non-UL 36C 28AWG, Alum-MyLar Foil Shielding with drain wire, OD: 8.5mm, Jacket: Beige	2m
3	Molded PVC Beige	-
	Molded PE Colour Transparent	
	Aluminium Foil 33×120mm	2
	Black PVC Tube 03×30mm	

Part Number Table

Description	Part Number
Computer Cable, 36 Way Centronics Plug to Plug, 2m, Grey	PC302

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
 Farnell.com/exclusive-brands
 Element14.com/exclusive-brands