9070TF500D33 TRANSFORMER CONTROL 500VA MULTIPLE VOLTAGES



Main

Enclosure type	Open box	
Range of product	TF	

Complementary

Depth	5.46 in (138.68 mm)
Device composition	Top fuse disconnector
Electrical connection	Screw clamp terminal
Fuse type	0.41 x 1.50 in CC top
Height	5.1 in (129.54 mm)
Material	Copper winding
Mounting support	panel
Phase	1 phase
Primary voltage	380/400/415 V
Rated power in VA	500 VA
Secondary voltage	115/230 V
Temperature rise	115 °C
Width	4.5 in (114.30 mm)

Environment

Insulation temperature	356 °F (180 °C)
Product certifications	UL listed file E61239 CE CSA file LR37055 guide 184-N-90
Standards	UL 508 NEC 450

Ordering and shipping details

Category	16203 - 9070 TF (NOT T) 250-1000VA
Discount Schedule	CP8
GTIN	00785901314479
Returnability	Yes
Country of origin	MX

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

18 months