

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRM21BZ70J226ME44# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-gb/products/productdetail?partno=GRM21BZ70J226ME44%23

GRM21BZ70J226ME44K

In Production RoHS REACH 125 Reflow OK Flow OK

< List of part numbers with package codes > GRM21BZ70J226ME44L GRM21BZ70J226ME44K

Appl

Applications

Unsuitable	Please be sure to read and comply with
Applications t	hese "Precautions for use."
Specific F Applications t	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical equipment [GHTF A/B/C] except for mplant equipment,Automotive nfotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about he performance, functions, quality, management, and safety required for he above applications, and use Products after confirming the performance and reliability of the actual Product.

Appearance & Shape



Notices


Temperature characteristic : Range of capacitance change rate is specified with 50% of rated voltage.



Packaging	Specifications	Standard Packing
		Quantity
L	180Embossed Tape	3000
К	330Embossed Tape	10000

ass (typ.)	
1 piece	23.0mg





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GRM21BZ70J226ME44K

Note: This datasheet may be out of date. Please download the latest datasheet of GRM21BZ70J226ME44# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRM21BZ70J226ME44%23

"#" indicates a package specification code.



Specifications

Length	2.0±0.2mm
Width	1.25±0.2mm
Thickness	1.25±0.2mm
Capacitance	22µF ±20%
Distance between external terminals g	0.7mm min.
External terminal size e	0.2 to 0.7mm
Operating Temperature Range	-55℃ to 125℃
Rated Voltage	6.3Vdc
Size code in inch(mm)	0805 (2012M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(Murata)
Temperature range of temperature characteristics	-55℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.