

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRM011R60J104ME01# from the official website of Murata Manufacturing Co., Ltd.

"#" indicates a package specification code.

http://www.murata.com/en-gb/products/productdetail?partno=GRM011R60J104ME01%23

# GRM011R60J104ME01L




#### < List of part numbers with package codes > GRM011R60J104ME01L

## Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Mobile Electronics	
	Please refer to Our Website and	
	specifications, etc. for information about	
Specific	the performance, functions, quality,	
· ·	management, and safety required for	
Applications	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

## Appearance & Shape





# Notices

Derating1. Only for mobile devices



### References

Packaging	Specifications	Standard Packing Quantity	
L	180Embossed Tape	50000	

Mass (typ.)	
1 piece	0.016mg

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GRM011R60J104ME01L

Note: This datasheet may be out of date. Please download the latest datasheet of GRM011R60J104ME01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=GRM011R60J104ME01%23

"#" indicates a package specification code.



### Specifications

Length	0.25±0.013mm
Width	0.125±0.013mm
Thickness	0.125±0.013mm
Capacitance	0.10µF ±20%
Distance between external terminals g	0.05mm min.
External terminal size e	0.05 to 0.1mm
Operating Temperature Range	-55°C to 85°C
Rated Voltage	6.3Vdc
Size code in inch(mm)	008004 (0201M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X5R(EIA)
Temperature range of temperature characteristics	-55°C to 85°C

#### 2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

