

# Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 2NC + 2NO, instantaneous, left side mounting, for GS1-GS2 with front/right handle

GS1AN22

Product availability : Stock - Normally stocked in distribution facility

## Main

Range of Product	TeSys
Device short name	GS1AN
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Contacts type and composition	2 NO + 2 NC
Contact operation	Instantaneous
[Ith] conventional free air thermal current	20 A 104 °F (40 °C)
[Ie] rated operational current	1 A 220 V DC-13 10 A 230 V AC-15 12 A 127 V AC-15 4 A 48 V DC-13 6 A 440 V AC-15 8 A 400/415 V AC-15 1.2 A 110 V DC-13

## Complementary

Range compatibility	TeSys (TeSys GS) fuse-switch disconnecter
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-15
Switch rated current	200 A 60 A 600 A 630 A 315 A 400 A 800 A 250 A 125 A 1250 A 160 A 50 A 63 A 100 A
Fuse type	DIN NFC BS
Type of operating handle	Direct frontal External frontal Direct right side External right side

Net Weight	0.52 lb(US) (0.238 kg)
------------	------------------------

### Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3389110563283
Returnability	No
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.77 in (4.5 cm)
Package 1 Width	2.76 in (7.0 cm)
Package 1 Length	5.12 in (13.0 cm)
Package 1 Weight	8.04 oz (228.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	12
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	6.50 lb(US) (2.95 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------

### Recommended replacement(s)